

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; Tl in HNO₃ 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS Reference Number: EQ0010
Issue date: 2016/9/7 Revision date: 2025/1/5 Supersedes version of: 2023/8/21 Version: 1.3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; Tl in HNO₃ 5% /tr HF Equivalent to Agilent Ref: 5188-6564
Product code : EQ0010

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Industrial use, Professional use
Use of the substance/mixture : Certified reference material for laboratory use
Function or use category : Laboratory chemicals

1.3. Details of the supplier of the safety data sheet

Spectracer UK Ltd.

20 Seymour Mews,
London,
W1H 6BQ,
United Kingdom.

Tel: +44 (0) 207 193 9114
Fax: +44 (0) 203 432 4686
Email: contact@spectracer.com
Web: www.spectracer.com

1.4. Emergency telephone number

Country/Area	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	: +353 1 8379964	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital Msida MSD 2090 Msida	112 +356 2545 6508	
United Kingdom	National Poisons Information Service (NHS Direct)	http://www.npis.org	111 (England & Wales only) or 112 (EU) or 08454 24 24 24 (Scotland)	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Corrosive to metals, Category 1 H290
Skin corrosion/irritation, Category 1, Sub-Category 1B H314
Serious eye damage/eye irritation, Category 1 H318
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

May be corrosive to metals. Causes severe skin burns and eye damage. Causes serious eye damage.

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; Tl in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS05

Signal word (CLP)

: Danger

Contains

: nitric acid

Hazard statements (CLP)

: H290 - May be corrosive to metals.

H314 - Causes severe skin burns and eye damage.

Precautionary statements (CLP)

: P260 - Do not breathe dusts or mists.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331+P310 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

Immediately call a POISON CENTER or doctor.

P303+P361+P353+P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a POISON CENTER or doctor.

P305+P351+P338+P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

P390 - Absorb spillage to prevent material damage.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	nitric acid (7697-37-2), hydrofluoric Acid (7664-39-3), lithium nitrate (7790-69-4) ⁽¹⁾ , yttrium trinitrate, hexahydrate (13494-98-9) ⁽¹⁾ , cobalt dinitrate (10141-05-6) ⁽¹⁾ , thallium nitrate (10102-45-1) ⁽¹⁾
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	nitric acid (7697-37-2), hydrofluoric Acid (7664-39-3), lithium nitrate (7790-69-4) ⁽¹⁾ , yttrium trinitrate, hexahydrate (13494-98-9) ⁽¹⁾ , cobalt dinitrate (10141-05-6) ⁽¹⁾ , thallium nitrate (10102-45-1) ⁽¹⁾

⁽¹⁾ Substance(s) in concentration below 0.1 % and displayed on a voluntary basis

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component	
Substance(s) not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	cobalt dinitrate (10141-05-6) ⁽¹⁾

⁽¹⁾ Substance(s) in concentration below 0.1 % and displayed on a voluntary basis

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
nitric acid substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PT, RO, SE, SI, SK, AL, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 7697-37-2 EC-No.: 231-714-2 EC Index-No.: 007-004-00-1 REACH-no: 01-2119487297-23-XXXX	5 – 10	Ox. Liq. 2, H272 Met. Corr. 1, H290 Acute Tox. 1 (Inhalation), H330 Skin Corr. 1A, H314 Eye Dam. 1, H318
hydrofluoric Acid substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, AL, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 7664-39-3 EC-No.: 231-634-8 EC Index-No.: 009-002-00-6 REACH-no: 01-2119458860-33-XXXX	0,1 – 0,25	Met. Corr. 1, H290 Acute Tox. 2 (Oral), H300 Acute Tox. 1 (Dermal), H310 Acute Tox. 2 (Inhalation), H330 Skin Corr. 1A, H314
lithium nitrate substance with national workplace exposure limit(s) (DE, SE, CH)	CAS-No.: 7790-69-4 EC-No.: 232-218-9	< 0,05	Ox. Sol. 3, H272 Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319
yttrium trinitrate, hexahydrate substance with national workplace exposure limit(s) (AT, BE, DK, ES, FI, FR, GB, GR, HR, IE, PL, PT, SI, IS, NO, MK)	CAS-No.: 13494-98-9 EC-No.: 233-802-6	< 0,05	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
cobalt dinitrate substance listed on REACH Candidate List (Cobalt(II) dinitrate) substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, GB, GR, HR, HU, IE, LV, NL, PT, RO, SE, IS, CH) Percentage by Weight of the metallic element: 0,00099851000000000%	CAS-No.: 10141-05-6 EC-No.: 233-402-1 EC Index-No.: 027-009-00-2	< 0,05	Ox. Sol. 2, H272 Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1, H317 Muta. 2, H341 Carc. 1B, H350i Repr. 1B, H360FD STOT RE Not classified Aquatic Acute 1, H400 Aquatic Chronic 1, H410
thallium nitrate substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DK, ES, FI, FR, GB, IE, PL, PT, RO, IS, NO, CH)	CAS-No.: 10102-45-1 EC-No.: 233-273-1 EC Index-No.: 081-002-00-9	< 0,05	Ox. Sol. 2, H272 Acute Tox. 2 (Oral), H300 Acute Tox. 2 (Inhalation), H330 STOT RE 2, H373 Aquatic Chronic 2, H411

Specific concentration limits:

Name	Product identifier	Specific concentration limits (%)
nitric acid	CAS-No.: 7697-37-2 EC-No.: 231-714-2 EC Index-No.: 007-004-00-1 REACH-no: 01-2119487297-23-XXXX	(5 ≤ C < 20) Skin Corr. 1B; H314 (20 ≤ C < 100) Skin Corr. 1A; H314 (65 ≤ C < 99) Ox. Liq. 3; H272 (99 ≤ C < 100) Ox. Liq. 2; H272

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
hydrofluoric Acid	CAS-No.: 7664-39-3 EC-No.: 231-634-8 EC Index-No.: 009-002-00-6 REACH-no: 01-2119458860-33-XXXX	(0,1 ≤ C < 1) Eye Irrit. 2; H319 (1 ≤ C < 7) Skin Corr. 1B; H314 (7 ≤ C < 100) Skin Corr. 1A; H314
cobalt dinitrate	CAS-No.: 10141-05-6 EC-No.: 233-402-1 EC Index-No.: 027-009-00-2	(0,01 ≤ C ≤ 100) Carc. 1B; H350i

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.
First-aid measures for first aider	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.
Absorb spillage to prevent material damage.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.
Storage conditions : Store in corrosive resistant container with a resistant inner liner. Keep only in original container. Store locked up.
Incompatible materials : Metals.
Packaging materials : Store always product in container of same material as original container.

Germany

Storage class (LGK, TRGS 510) : LGK 8B - Non-combustible corrosive substances

Joint storage table

LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for : LGK 1, LGK 5.1A, LGK 5.2, LGK 6.2, LGK 7
Joint storage with restrictions permitted for : LGK 4.1A, LGK 4.2, LGK 4.3, LGK 5.1C
Joint storage permitted for : LGK 2A, LGK 2B, LGK 3, LGK 4.1B, LGK 5.1B, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK 10-13

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

nitric acid (7697-37-2)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Nitric acid
IOEL STEL	2,6 mg/m ³
	1 ppm
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
Albania - Occupational Exposure Limits	
Local name	Acid nitrik
OEL STEL	2,6 mg/m ³
	1 ppm
Regulatory reference	VENDIM Nr. 522, datë 6.8.2014 PËR MIRATIMIN E RREGULLORES "PËR MBROJTJEN E SIGURISË DHE SHËNDETIT TË PUNËMARRËSVE NGA RISQET E LIDHURA ME AGJENTËT KIMIKË NË PUNË"
Austria - Occupational Exposure Limits	
Local name	Salpetersäure
OEL C	2,6 mg/m ³
	1 ppm
Regulatory reference	BGBI. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	Acide nitrique # Salpeterzuur
OEL STEL	2,6 mg/m ³
	1 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
Bulgaria - Occupational Exposure Limits	
Local name	Азотна киселина
OEL STEL	2,6 mg/m ³
	1 ppm
Remark	• (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 28 от 2024 г., в сила от 05.04.2024 г.)
Croatia - Occupational Exposure Limits	
Local name	Dušična kiselina

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

nitric acid (7697-37-2)	
KGVI (OEL STEL)	2,6 mg/m ³
	1 ppm
Remark	Direktiva: 2006/15/EZ
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 148/2023)
Cyprus - Occupational Exposure Limits	
Local name	Νιτρικό οξύ
OEL STEL	2,6 mg/m ³
	1 ppm
Regulatory reference	Κανονισμοί του 2007 (Κ.Δ.Π. 295/2007)
Czech Republic - Occupational Exposure Limits	
Local name	Kyselina dusičná
PEL (OEL TWA)	1 mg/m ³
	0,38 ppm
NPK-P (OEL C)	2,5 mg/m ³
	0,95 ppm
Remark	I - dráždí sliznice (oči, dýchací cesty) resp. kůže.
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 330/2023 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Salpetersyre
OEL STEL	2,6 mg/m ³
	1 ppm
Remark	E (betyder, at stoffet har en EF-grænseværdi); S (betyder, at grænseværdien ikke bør overskrides. Værdien gælder for en eksponeringsperiode på 15 minutter)
Regulatory reference	BEK nr 291 af 19/03/2024
Estonia - Occupational Exposure Limits	
Local name	Lämmastikhape
OEL STEL	2,6 mg/m ³
	1 ppm
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 02.04.2024, 13)
Finland - Occupational Exposure Limits	
Local name	Typpihappo
HTP (OEL TWA)	1,3 mg/m ³
	0,5 ppm
HTP (OEL STEL)	2,6 mg/m ³
	1 ppm
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

nitric acid (7697-37-2)	
France - Occupational Exposure Limits	
Local name	Acide nitrique
VLE (OEL C/STEL)	2,6 mg/m ³
	1 ppm
Remark	Valeurs réglementaires indicatives
Regulatory reference	Arrêté du 30 juin 2004 modifié (réf.: INRS ED 6443, 2022; Outil65; Arrêté du 26 octobre 2007)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Salpetersäure
AGW (OEL TWA)	2,6 mg/m ³
	1 ppm
Remark	EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); 13 - Eine Begründung für die Ableitung eines gesundheitsbasierten AGW liegt nicht vor; 16 - Der Arbeitsplatzgrenzwert ist nur als Kurzzeitwert festgelegt. Die betriebliche Überwachung soll durch messtechnische Mittelwertbildung über 15 Minuten erfolgen, z.B. durch eine 15-minütige Probenahme
Regulatory reference	TRGS900
Gibraltar - Occupational Exposure Limits	
Local name	Nitric acid
OEL STEL	2,6 mg/m ³
	1 ppm
Regulatory reference	Factories (Control of Chemical Agents at Work) Regulations 2003 (LN. 2018/181)
Greece - Occupational Exposure Limits	
Local name	Νιτρικό οξύ
OEL STEL	2,6 mg/m ³
	1 ppm
Regulatory reference	Π.Δ. 162/2007 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
Local name	SALÉTRÓMSAV
CK (OEL STEL)	2,6 mg/m ³
Remark	i (ingerlő anyag, amely izgatja a bőrt, nyálkahártyát, szemet vagy mindhármát), m (maró hatású anyag, amely felmarja a bőrt, nyálkahártyát, szemet vagy mindhármát); EU2 (2006/15/EK irányelvben közölt érték)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	Nitric acid
OEL STEL	2,6 mg/m ³
	1 ppm
Remark	IOELV (Indicative Occupational Exposure Limit Values)

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

nitric acid (7697-37-2)	
Regulatory reference	Chemical Agents Code of Practice 2024
Italy - Occupational Exposure Limits	
Local name	Acido nitrico
OEL STEL	2,6 mg/m ³ 1 ppm
Regulatory reference	Allegato XXXVIII del Decreto Legislativo 4 settembre 2024, n. 135
Latvia - Occupational Exposure Limits	
Local name	Slāpekšķābe
OEL TWA	2 mg/m ³ 0,78 ppm
OEL STEL	2,6 mg/m ³ 1 ppm
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325 (Grozījumi Ministru kabineta 2024. gada 26. martā noteikumiem Nr. 191).
Lithuania - Occupational Exposure Limits	
Local name	Nitrato rūgštis (azoto rūgštis)
TPRV (OEL STEL)	2,6 mg/m ³ 1 ppm
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Luxembourg - Occupational Exposure Limits	
Local name	Acide nitrique
OEL STEL	2,6 mg/m ³ 1 ppm
Regulatory reference	Mémorial A N° 226 de 2021 concernant la protection de la sécurité et de la santé des salariés contre les risques liés à des agents chimiques sur le lieu de travail
Malta - Occupational Exposure Limits	
Local name	Nitric acid
OEL STEL	2,6 mg/m ³ 1 ppm
Regulatory reference	S.L. 424.24 - Chemical Agents at Work Regulations (L.N. 356 of 2021) # L.S. 424.24 - Regolamenti dwar Aġenti Kimiċi fuq il-Post tax-Xogħol (A.L. 356 tal-2021)
Netherlands - Occupational Exposure Limits	
Local name	Salpeterzuur
TGG-15min (OEL STEL)	1,3 mg/m ³ 0,5 ppm (Salpeterzuur; Netherlands; Short time value; Public occupational exposure limit value)
Regulatory reference	Arbeidsomstandighedenregeling 2024
Portugal - Occupational Exposure Limits	
Local name	Ácido nítrico

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

nitric acid (7697-37-2)	
OEL TWA	2 ppm
OEL STEL	4 ppm
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Acid nitric/Acid azotic
OEL STEL	2,6 mg/m ³ 1 ppm
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 179/2024)
Serbia - Occupational Exposure Limits	
Local name	азотна киселина
OEL STEL	3 mg/m ³ 1 ppm
Remark	ЕУ** – напомена да се ради о хемијским материјама за које су утврђене индикативне граничне вредности изложености према Директиви 2006/15/ЕЗ (друга листа)
Regulatory reference	ПРАВИЛНИК о превентивним мерама за безбедан и здрав рад при излагању хемијским материјама („Службени гласник РС”, бр. 106/09, 117/17 и 107/21)
Slovakia - Occupational Exposure Limits	
Local name	Kyselina dusičná
NPHV (OEL STEL)	2,6 mg/m ³ 1 ppm
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (122/2024 Z. z.)
Slovenia - Occupational Exposure Limits	
Local name	dušikova kislina
OEL TWA	2,6 mg/m ³ 1 ppm
OEL STEL	2,6 mg/m ³ 1 ppm
Remark	EU
Regulatory reference	Uradni list RS, št. 29/2024 z dne 4. 4. 2024 - Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu
Spain - Occupational Exposure Limits	
Local name	Ácido nítrico
VLA-EC (OEL STEL)	2,6 mg/m ³ 1 ppm
Remark	VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2024. INSHT
Sweden - Occupational Exposure Limits	
Local name	Salpetersyra
NGV (OEL TWA)	1,3 mg/m ³

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

nitric acid (7697-37-2)	
	0,5 ppm
KGV (OEL STEL)	2,6 mg/m ³
	1 ppm
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	Nitric acid
WEL STEL (OEL STEL)	2,6 mg/m ³
	1 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Iceland - Occupational Exposure Limits	
Local name	Saltpéturssýra
OEL STEL	2,6 mg/m ³
	1 ppm
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
Norway - Occupational Exposure Limits	
Local name	Salpetersyre
Grenseverdi (OEL TWA)	5 mg/m ³
	2 ppm
Remark	E: EU har en veiledende grenseverdi og/eller anmerkning for stoffet.
Regulatory reference	FOR-2024-04-05-581
North Macedonia - Occupational Exposure Limits	
Local name	азотна киселина
OEL TWA	2,6 mg/m ³
	1 ppm
KTV	1
Short time value [mg/m ³]	2,6 mg/m ³
Short time value [ppm]	1 ppm
Remark	(KTV) краткотрајна вредност (КТВ) значи концентрација на опасни хемиски супстанции во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покусо време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m ³ или во ml/m ³ (ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност; (EU) European Union – гранична вредност, определена на ниво на Европската унија; (*) дополнување на граничната вредност заради донесената Директива на Комисијата 2006/15ES од 7 февруари 2006 за создавање на втора листа на индикативни гранични вредности за професионална изложеност според директивата 98/24/ЕС и за измените на директивата 91/322/ЕЕС и директивата 2000/39/ ЕС (Сл. весник бр. 38 од ден 9.2.2006, стр. 36)

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

nitric acid (7697-37-2)	
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)
Switzerland - Occupational Exposure Limits	
Local name	Acide nitrique / Salpetersäure
MAK (OEL TWA)	5 mg/m ³ 2 ppm
KZGW (OEL STEL)	5 mg/m ³ 2 ppm
Remark	NIOSH, OSHA
Regulatory reference	www.suva.ch, 01.01.2024
USA - ACGIH - Occupational Exposure Limits	
Local name	Nitric acid
ACGIH OEL TWA	2 ppm
ACGIH OEL STEL	4 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr; dental erosion
Regulatory reference	ACGIH 2024
hydrofluoric Acid (7664-39-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Hydrogen fluoride
IOEL TWA	1,5 mg/m ³ 1,8 ppm
IOEL STEL	2,5 mg/m ³ 3 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
EU - Biological Limit Value (BLV)	
Local name	Hydrogen fluoride
BLV	8 mg/l Parameter: F - Medium: urine - Sampling time: end of shift
Regulatory reference	SCOEL List of recommended health-based BLVs and BGVs
Albania - Occupational Exposure Limits	
Local name	Fluorur hidrogjeni
OEL TWA	1,5 mg/m ³ 1,8 ppm
OEL STEL	2,5 mg/m ³ 3 ppm
Regulatory reference	VENDIM Nr. 522, datë 6.8.2014 PËR MIRATIMIN E RREGULLORES “PËR MBROJTJEN E SIGURISË DHE SHËNDETIT TË PUNËMARRËSVE NGA RISQET E LIDHURA ME AGJENTËT KIMIKË NË PUNË”

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

hydrofluoric Acid (7664-39-3)	
Austria - Occupational Exposure Limits	
Local name	Fluorwasserstoff (Flusssäure; Hydrogenfluorid)
MAK (OEL TWA)	1,5 mg/m ³
	1,8 ppm
MAK (OEL STEL)	2,5 mg/m ³ (4x 15(Miw) min)
	3 ppm (4x 15(Miw) min)
Remark	H
Regulatory reference	BGBl. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	Hydrogène (fluorure d') # Waterstofffluoride
OEL TWA	1,5 mg/m ³
	1,8 ppm
OEL STEL	2,5 mg/m ³
	3 ppm
Remark	M: la mention "M" indique que lors d'une exposition supérieure à la valeur limite, des irritations apparaissent ou un danger d'intoxication aiguë existe. Le procédé de travail doit être conçu de telle façon que l'exposition ne dépasse jamais la valeur limite. Lors des mesurages, la période d'échantillonnage doit être aussi courte que possible afin de pouvoir effectuer des mesurages fiables. Le résultat des mesurages est calculé en fonction de la période d'échantillonnage. # M: de vermelding "M" duidt aan dat bij de blootstelling boven de grenswaarde irritatie optreedt of er gevaar bestaat voor acute vergiftiging. Het werkprocédé moet zo zijn ontworpen dat de blootstelling de grenswaarde nooit overschrijdt. Bij een controle geldt dat de bemonsterde periode zo kort mogelijk moet zijn om een betrouwbare meting te kunnen verrichten. Het meetresultaat wordt dan gerelateerd aan de beschouwde periode.
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
Bulgaria - Occupational Exposure Limits	
Local name	Флуороводород
OEL TWA	1,5 mg/m ³
	1,8 ppm
OEL STEL	2,5 mg/m ³
	3 ppm
Remark	• (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 28 от 2024 г., в сила от 05.04.2024 г.)
Croatia - Occupational Exposure Limits	
Local name	Vodikov fluorid
GVI (OEL TWA)	1,5 mg/m ³
	1,8 ppm
KGVI (OEL STEL)	2,5 mg/m ³

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

hydrofluoric Acid (7664-39-3)	
	3 ppm
Remark	Direktiva: 2000/39/EZ
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 148/2023)
Croatia - Biological limit values	
Local name	Fluorovodična kiselina (vodikov fluorid) i anorganski fluorovi spojevi
BLV	8 mg/g creatinine Karakteristični pokazatelj: fluoridi - Biološki uzorak: mokraća - Vrijeme uzorkovanja: na kraju radne smjene 40 mmol/mol Creatinine Karakteristični pokazatelj: fluoridi - Biološki uzorak: mokraća - Vrijeme uzorkovanja: na kraju radne smjene 4 mg/g creatinine Karakteristični pokazatelj: fluoridi - Biološki uzorak: mokraća - Vrijeme uzorkovanja: prije početka radne smjene u sredini tjedna 24 mmol/mol Creatinine Karakteristični pokazatelj: fluoridi - Biološki uzorak: mokraća - Vrijeme uzorkovanja: prije početka radne smjene u sredini tjedna
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 91/2018)
Cyprus - Occupational Exposure Limits	
Local name	Υδροφθόριο
OEL TWA	1,5 mg/m ³ 1,8 ppm
OEL STEL	2,5 mg/m ³ 3 ppm
Regulatory reference	Κανονισμοί του 2007 (Κ.Δ.Π. 295/2007)
Czech Republic - Occupational Exposure Limits	
Local name	Fluorovodík
PEL (OEL TWA)	1,5 mg/m ³ 1,8 ppm
NPK-P (OEL C)	2,5 mg/m ³ 3 ppm
Remark	I - dráždí sliznice (oči, dýchací cesty) resp. kůži.
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 330/2023 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Hydrogenfluorid (Fluorbrinte)
OEL TWA	1,5 mg/m ³ 1,8 ppm
OEL STEL	3 mg/m ³ 2,5 ppm
Remark	E (betyder, at stoffet har en EF-grænseværdi)
Regulatory reference	BEK nr 291 af 19/03/2024
Estonia - Occupational Exposure Limits	
Local name	Vesinikfluoriid

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

hydrofluoric Acid (7664-39-3)	
OEL TWA	1,5 mg/m ³
	1,8 ppm
OEL STEL	2,5 mg/m ³
	3 ppm
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 02.04.2024, 13)
Finland - Occupational Exposure Limits	
Local name	Fluorivety
HTP (OEL TWA)	1,5 mg/m ³
	1,8 ppm
HTP (OEL STEL)	2,5 mg/m ³
	3 ppm
Remark	lho
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveystieteiden ministeriö)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Fluorwasserstoff
AGW (OEL TWA)	0,83 mg/m ³
	1 ppm
Peak exposure limitation factor	2(l)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden; H - hautresorptiv
Regulatory reference	TRGS900
Germany - Biological limit values (TRGS 903)	
Local name	Hydrogenfluorid (Fluorwasserstoff) und anorganische Fluorverbindungen (Fluoride)
Biological limit value	4 mg/l Parameter: Fluorid - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende - Festlegung/Begründung: 11/2020 DFG
Regulatory reference	TRGS 903
Gibraltar - Occupational Exposure Limits	
Local name	Hydrogen fluoride
OEL TWA	1,5 mg/m ³
	1,8 ppm
OEL STEL	2,5 mg/m ³
	3 ppm
Regulatory reference	Factories (Control of Chemical Agents at Work) Regulations 2003 (LN. 2018/181)
Greece - Occupational Exposure Limits	
Local name	Υδροφθόριο
OEL TWA	2,5 mg/m ³
	3 ppm

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

hydrofluoric Acid (7664-39-3)	
OEL STEL	2,5 mg/m ³
	3 ppm
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
Local name	HIDROGÉN-FLUORID
AK (OEL TWA)	1,5 mg/m ³
CK (OEL STEL)	2,5 mg/m ³
Remark	b (Bőrön át is felszívódik), m (maró hatású anyag, amely felmarja a bőrt, nyálkahártyát, szemet vagy mindhármat), BEM (biológiai expozíciós mutató); EU1 (2000/39/EK irányelvben közölt érték); N (Irritáló anyagok, egyszerű fojtógázok, csekély egészségkárosító hatással bíró anyagok)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	Hydrogen fluoride (as F)
OEL TWA	1,5 mg/m ³
	1,8 ppm
OEL STEL	2,5 mg/m ³
	3 ppm
Remark	IOELV (Indicative Occupational Exposure Limit Values), Skin (Substances which have the capacity to penetrate intact skin when they come in contact with it and be absorbed into the body. A substantial contribution to the total body burden via dermal exposure is possible)
Regulatory reference	Chemical Agents Code of Practice 2024
Italy - Occupational Exposure Limits	
Local name	Acido fluoridrico
OEL TWA	1,5 mg/m ³
	1,8 ppm
OEL STEL	2,5 mg/m ³
	3 ppm
Regulatory reference	Allegato XXXVIII del Decreto Legislativo 4 settembre 2024, n. 135
Latvia - Occupational Exposure Limits	
Local name	Fluorūdeņradis
OEL TWA	1,5 mg/m ³
	1,8 ppm
OEL STEL	2,5 mg/m ³
	3 ppm
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325 (Grozījumi Ministru kabineta 2024. gada 26. martā noteikumiem Nr. 191).

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

hydrofluoric Acid (7664-39-3)	
Lithuania - Occupational Exposure Limits	
Local name	Vandenilio fluoridas
IPRV (OEL TWA)	1,5 mg/m ³
	1,8 ppm
TPRV (OEL STEL)	2,5 mg/m ³
	3 ppm
Remark	Ū (ūmus poveikis)
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Luxembourg - Occupational Exposure Limits	
Local name	Fluorure d'hydrogène
OEL TWA	1,5 mg/m ³
	1,8 ppm
OEL STEL	2,5 mg/m ³
	3 ppm
Regulatory reference	Mémorial A N° 226 de 2021 concernant la protection de la sécurité et de la santé des salariés contre les risques liés à des agents chimiques sur le lieu de travail
Malta - Occupational Exposure Limits	
Local name	Hydrogen fluoride
OEL TWA	1,5 mg/m ³
	1,8 ppm
OEL STEL	2,5 mg/m ³
	3 ppm
Regulatory reference	S.L. 424.24 - Chemical Agents at Work Regulations (L.N. 356 of 2021) # L.S. 424.24 - Regolamenti dwar Aġenti Kimiċi fuq il-Post tax-Xogħol (A.L. 356 tal-2021)
Netherlands - Occupational Exposure Limits	
Local name	Fluorwaterstof
TGG-15min (OEL STEL)	1 mg/m ³ (als F)
	1,2 ppm (Fluorwaterstof (als F); Netherlands; Short time value; Public occupational exposure limit value; als F)
Regulatory reference	Arbeidsomstandighedenregeling 2024
Poland - Occupational Exposure Limits	
Local name	Fluorowodór
NDS (OEL TWA)	0,5 mg/m ³
NDSCh (OEL STEL)	2 mg/m ³
Regulatory reference	Dz. U. 2024 poz. 1017 wraz z późn. zm.
Portugal - Occupational Exposure Limits	
Local name	Ácido fluorídrico, expresso em F
OEL TWA	0,5 ppm
OEL C	2 mg/m ³

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

hydrofluoric Acid (7664-39-3)	
	2 ppm
Remark	P (Toxicidade percutânea); IBE (Índice biológico de exposição)
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Acid fluorhidric/Fluorură de hidrogen
OEL TWA	1,5 mg/m ³
	1,8 ppm
OEL STEL	2,5 mg/m ³
	3 ppm
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 179/2024)
Serbia - Occupational Exposure Limits	
Local name	водоник флуорид, флуороводоник
OEL TWA	2 mg/m ³
	2 ppm
OEL STEL	3 mg/m ³
	3 ppm
Remark	EУ* – напомена да се ради о хемијским материјама за које су утврђене индикативне граничне вредности изложености према Директиви 2000/39/ЕЗ (прва листа)
Regulatory reference	ПРАВИЛНИК о превентивним мерама за безбедан и здрав рад при излагању хемијским материјама („Службени гласник РС”, бр. 106/09, 117/17 и 107/21)
Slovakia - Occupational Exposure Limits	
Local name	Fluórovodík, kyselina fluorovodíková (ako F)
NPHV (OEL TWA)	1,5 mg/m ³
	1,8 ppm
NPHV (OEL STEL)	2,5 mg/m ³
	3 ppm
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (122/2024 Z. z.)
Slovakia - Biological limit values	
Local name	Fluorovodík a anorganické zlúčeniny fluóru (fluoridy)
BLV	7 mg/g creatinine Zisťovaný faktor: Fluoridy - Vyšetovaný materiál: moč - Čas odberu vzorky: b) koniec expozície alebo pracovnej zmeny 4 mg/g creatinine Zisťovaný faktor: Fluoridy - Vyšetovaný materiál: moč - Čas odberu vzorky: d) pred nasledujúcou pracovnou zmenou
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (122/2024 Z. z.)
Slovenia - Occupational Exposure Limits	
Local name	vodikov fluorid
OEL TWA	1,5 mg/m ³
	1,8 ppm
OEL STEL	2,25 mg/m ³
	2,7 ppm

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

hydrofluoric Acid (7664-39-3)	
Remark	K (Lastnost lažjega prehajanja snovi v organizem skozi kožo), Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti), BAT (Biološka mejna vrednost), EU
Regulatory reference	Uradni list RS, št. 29/2024 z dne 4. 4. 2024 - Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu
Slovenia - Biological limit values	
Local name	vodikov fluorid in anorganske fluorove spojine (fluoridi)
BLV	7 mg/g creatinine Parameter: fluorid - Biološki vzorec: urin - Čas vzorčenja: ob koncu delovne izmene 4 mg/g creatinine Parameter: fluorid - Biološki vzorec: urin - Čas vzorčenja: pred naslednjim delovnim dnevom
Regulatory reference	Uradni list RS, št. 29/24 z dne 4. 4. 2024 - Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu
Spain - Occupational Exposure Limits	
Local name	Fluoruro de hidrógeno
VLA-ED (OEL TWA)	1,5 mg/m ³ 1,8 ppm
VLA-EC (OEL STEL)	2,5 mg/m ³ 3 ppm
Remark	VLB® (Agente químico que tiene Valor Límite Biológico), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2024. INSHT
Spain - Biological limit values	
Local name	Fluoruro de hidrógeno
BLV	2 mg/l Parámetro: Fluoruros - Medio: Orina - Momento de muestreo: Antes de la jornada laboral - Notas: F (Fondo. El indicador está generalmente presente en cantidades detectables en personas no expuestas laboralmente. Estos niveles de fondo están considerados en el valor VLB), I (Significa que el indicador biológico es inespecífico puesto que puede encontrarse después de la exposición a otros agentes químicos) 3 mg/l Parámetro: Fluoruros - Medio: Orina - Momento de muestreo: Final de la jornada laboral - Notas: F (Fondo. El indicador está generalmente presente en cantidades detectables en personas no expuestas laboralmente. Estos niveles de fondo están considerados en el valor VLB), I (Significa que el indicador biológico es inespecífico puesto que puede encontrarse después de la exposición a otros agentes químicos)
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2024. INSHT
Sweden - Occupational Exposure Limits	
Local name	Vätefluorid (Fluorväte)
NGV (OEL TWA)	1,5 mg/m ³ 1,8 ppm
KGV (OEL STEL)	1,7 mg/m ³ 2 ppm
Remark	31 (Vid exponering för blandningar av fluorider och vätefluorid ska nivågränsvärdet för fluorider tillämpas)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

hydrofluoric Acid (7664-39-3)	
United Kingdom - Occupational Exposure Limits	
Local name	Hydrogen fluoride
WEL TWA (OEL TWA)	1,5 mg/m ³ (as F)
	1,8 ppm (as F)
WEL STEL (OEL STEL)	2,5 mg/m ³ (as F)
	3 ppm (as F)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Iceland - Occupational Exposure Limits	
Local name	Vetnisflúoríð (flúorvetni)
OEL TWA	0,6 mg/m ³
	0,7 ppm
OEL STEL	2,5 mg/m ³ Þakgildið er miðað við fimm mínútna tímabil
	3 ppm Þakgildið er miðað við fimm mínútna tímabil
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
Norway - Occupational Exposure Limits	
Local name	Hydrogenfluorid (Fluss-syre)
Grenseverdi (OEL TWA)	0,5 mg/m ³
	0,6 ppm
Korttidsverdi (OEL STEL)	1,5 mg/m ³
	1,8 ppm
Remark	H: Kjemikalier som kan tas opp gjennom huden; E: EU har en veiledende grenseverdi og/eller anmerkning for stoffet.
Regulatory reference	FOR-2024-04-05-581
North Macedonia - Occupational Exposure Limits	
Local name	Флуороводород
OEL TWA	1,5 mg/m ³
	1,8 ppm
KTV	1,5
Short time value [mg/m ³]	2,25 mg/m ³
Short time value [ppm]	2,7 ppm

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

hydrofluoric Acid (7664-39-3)	
Remark	(КТВ) краткотрајна вредност (КТВ) значи концентрација на опасни хемиски супстанции во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покусо време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m ³ или во ml/m ³ (ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност; (БАТ) биолошка гранична вредност – праг на биолошка гранична вредност, што значи предупредување на опасна хемиска супстанца и нејзини метаболити во ткивата, телесните течности или издишувањето на воздухот, без оглед на тоа, дали опасната хемиска супстанца е внесена во организмот со вдишување, голтање или преку кожата; (EU) European Union – гранична вредност, определена на ниво на Европската унија
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија” бр.46/10)
Switzerland - Occupational Exposure Limits	
Local name	Acide fluorhydrique / Fluorwasserstoff
MAK (OEL TWA)	0,83 mg/m ³ 1 ppm
KZGW (OEL STEL)	1,66 mg/m ³ 2 ppm
Notation	SS _c , B / SS _c , B
Remark	HSE, NIOSH, OSHA
Regulatory reference	www.suva.ch, 01.01.2024
Switzerland - BAT	
Local name	Fluorures / Fluorwasserstoff
BAT	4 mg/l (211 µmol/l; Paramètre biologique: Fluorures; Substrat d'examen: Urine; Moment du prélèvement: Fin de l'exposition, de la période de travail.) / (211 µmol/l; Biologischer Parameter: Fluorid; Untersuchungsmaterial: Urin; Probennahmezeitpunkt: Expositionsende, bzw. Schichtende.)
Remark	Influence de l'environnement. / Umwelteinflüsse.
Regulatory reference	Ordonnance 832.30 (OPA), article 50 al. 3, www.suva.ch/valeurs-limites / Verordnung 832.30 (VUV), Art. 50 Abs. 3, www.suva.ch/grenzwerte
USA - ACGIH - Occupational Exposure Limits	
Local name	Hydrogen fluoride, as F
ACGIH OEL TWA	0,5 ppm
ACGIH OEL C	2 ppm
Remark (ACGIH)	TLV® Basis: URT, LRT, skin, & eye irr; fluorosis. Notations: Skin; BEI
Regulatory reference	ACGIH 2024
lithium nitrate (7790-69-4)	
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Lithiumverbindungen, anorganische, mit Ausnahme von Lithium und stärker reizenden Lithiumverbindungen

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

lithium nitrate (7790-69-4)	
AGW (OEL TWA)	0,2 mg/m ³ (E)
Peak exposure limitation factor	1(l)
Remark	Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden; 10 - Der Arbeitsplatzgrenzwert bezieht sich auf den Elementgehalt des entsprechenden Metalls; DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission)
Regulatory reference	TRGS900
Sweden - Occupational Exposure Limits	
Local name	Litium och föreningar (som Li)
KGW (OEL STEL)	0,02 mg/m ³ inhalerbar fraktion
Remark	3 (Med inhalerbar fraktion menas den mängd partiklar, av totalmängden partiklar i luften, som man inandas genom näsa och mun)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
Switzerland - Occupational Exposure Limits	
Local name	Lithium, comp. inorg. De / Lithiumverbindungen, anorganische
MAK (OEL TWA)	0,2 mg/m ³ (i) / (e)
KZGW (OEL STEL)	0,2 mg/m ³ (i) / (e)
Notation	SS _c / SS _c
Remark	OSHA. Exprimé en Li / OSHA. Als Li berechnet
Regulatory reference	www.suva.ch, 01.01.2024
yttrium trinitrate, hexahydrate (13494-98-9)	
Austria - Occupational Exposure Limits	
Local name	Yttrium
MAK (OEL TWA)	1 mg/m ³
MAK (OEL STEL)	10 mg/m ³
Regulatory reference	BGBl. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	Yttrium (métal et composés) (en Y) # Yttrium (metaal en verbindingen) (als Y)
OEL TWA	1 mg/m ³
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
Croatia - Occupational Exposure Limits	
Local name	Itrij
GVI (OEL TWA)	1 mg/m ³
KGVI (OEL STEL)	3 mg/m ³
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 148/2023)
Denmark - Occupational Exposure Limits	
Local name	Yttrium, pulver og forbindelser
OEL TWA	1 mg/m ³ beregnet som Y

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

yttrium trinitrate, hexahydrate (13494-98-9)	
Regulatory reference	BEK nr 291 af 19/03/2024
Finland - Occupational Exposure Limits	
Local name	Yttrium, metalli
HTP (OEL TWA)	1 mg/m ³
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
France - Occupational Exposure Limits	
Local name	Yttrium
VME (OEL TWA)	1 mg/m ³
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 6443, 2022; Outil65)
Greece - Occupational Exposure Limits	
Local name	Υττριο και ενώσεις του
OEL TWA	5 mg/m ³
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Ireland - Occupational Exposure Limits	
Local name	Yttrium
OEL TWA	1 mg/m ³
OEL STEL	3 mg/m ³
Remark	Advisory OELV (Advisory Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2024
Poland - Occupational Exposure Limits	
Local name	Itr i jego związki w przeliczeniu na Y
NDS (OEL TWA)	1 mg/m ³
Regulatory reference	Dz. U. 2024 poz. 1017 wraz z późn. zm.
Portugal - Occupational Exposure Limits	
Local name	Ítrio e compostos, expressos em Y
OEL TWA	1 mg/m ³
Regulatory reference	Norma Portuguesa NP 1796:2014
Slovenia - Occupational Exposure Limits	
Local name	itrij
OEL TWA	5 mg/m ³
OEL STEL	20 mg/m ³
Spain - Occupational Exposure Limits	
Local name	Itrio
VLA-ED (OEL TWA)	1 mg/m ³ metal 1 mg/m ³ Compuestos de itrio, como Y
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2024. INSHT

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

yttrium trinitrate, hexahydrate (13494-98-9)	
United Kingdom - Occupational Exposure Limits	
Local name	Yttrium
WEL TWA (OEL TWA)	1 mg/m ³
WEL STEL (OEL STEL)	3 mg/m ³
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Iceland - Occupational Exposure Limits	
Local name	Yttríum, duft og sambönd, sem Y
OEL TWA	1 mg/m ³
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
Norway - Occupational Exposure Limits	
Local name	Yttrium
Grenseverdi (OEL TWA)	1 mg/m ³
Regulatory reference	FOR-2024-04-05-581
North Macedonia - Occupational Exposure Limits	
Local name	итриум
OEL TWA	5 mg/m ³ (l) инхалабилна фракција – дел на вкупно суспендирани материи, кои работникот ги вдишува
KTV	4
Short time value [mg/m ³]	20 mg/m ³
Remark	(KTV) краткотрајна вредност (КТВ) значи концентрација на опасни хемиски супстанции во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покусо време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m ³ или во ml/m ³ (ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)
USA - ACGIH - Occupational Exposure Limits	
Local name	Yttrium
ACGIH OEL TWA	1 mg/m ³
Remark (ACGIH)	Pulm fibrosis
Regulatory reference	ACGIH 2024
cobalt dinitrate (10141-05-6)	
Austria - Occupational Exposure Limits	
Local name	Cobalt und seine Verbindungen (Cobalt als Cobaltmetall, Cobaltoxid, Cobaltsulfid und Cobaltsulfat, Staub von Cobaltlegierungen)
TRK (OEL TWA)	0,5 mg/m ³ (Herstellung von Cobaltpulver und Katalysatoren, Hartmetallund) (als Co berechnet, E) 0,1 mg/m ³ (im übrigen) (als Co berechnet, E)

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

cobalt dinitrate (10141-05-6)	
TRK (OEL STEL)	2 mg/m ³ (Herstellung von Cobaltpulver und Katalysatoren, Hartmetallund) (als Co berechnet, E, 4x 15(Miw) min) 0,4 mg/m ³ (im übrigen) (als Co berechnet, E, 4x 15(Miw) min)
Remark	H, Sah. Krebs erzeugend: III A2
Regulatory reference	BGBl. II Nr. 156/2021
Austria - Biological limit values	
Local name	Cobalt und seine Verbindungen
BLV	10 µg/l Parameter: Cobalt - Untersuchungsmaterial: Harn
Remark	Eignung mit vorzeitiger Folgeuntersuchung: Überschreiten des Grenzwertes für Cobalt im Harn. Bei Vorliegen einer wesentlichen Beeinträchtigung der Lungenfunktion. Diese liegt vor, wenn nach mehrmaliger Messung der beste gemessene Wert den für den/die Untersuchte/n maßgebenden Sollwert um 20% unterschreitet, bzw. den MEF50-Sollwert um 50% unterschreitet. Eine vorzeitige Folgeuntersuchung ist jedoch nicht erforderlich, wenn im Vergleich zu Vorbefunden der altersabhängige physiologische Abfall der 1 Sekundenkapazität (FEV1) von 40 ml/Jahr nicht überschritten wird oder aus der Beurteilung des Kurvenverlaufes der Forcierten Vitalkapazität (FVC) eine eingeschränkte Mitarbeit des Untersuchten/der Untersuchten ersichtlich ist. Der Zeitabstand zwischen den Untersuchungen beträgt bei Eignung: ein Jahr, bei Eignung mit vorzeitiger Folgeuntersuchung: sechs Monate.
Regulatory reference	Verordnung über die Gesundheitsüberwachung am Arbeitsplatz 2017 (VGÜ 2017)
Belgium - Occupational Exposure Limits	
Local name	Cobalt métal (fumées et poussières) (en Co) # Kobaltmetaal (stof en rook) als Co
OEL TWA	0,02 mg/m ³
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
Bulgaria - Occupational Exposure Limits	
Local name	Кобалт
OEL TWA	0,1 mg/m ³ (и неорганични съединения (като кобалт))
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 28 от 2024 г., в сила от 05.04.2024 г.)
Croatia - Occupational Exposure Limits	
Local name	Kobalt i spojevi (kao Co)
GVI (OEL TWA)	0,1 mg/m ³
Remark	Alergen (koža (tvar koja može izazvati alergijsku reakciju na koži (H317)) i udisanje (tvar koja udisanjem može izazvati simptome alergije ili astme ili poteškoće s disanjem (H334)))
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, граничним vrijednostima izloženosti i biološkim граничним vrijednostima (NN 148/2023)
Czech Republic - Occupational Exposure Limits	
Local name	Kobalt a jeho sloučeniny, jako Co
PEL (OEL TWA)	0,05 mg/m ³ (V - vdechovatelná frakce aerosolu)
NPK-P (OEL C)	0,1 mg/m ³ (V - vdechovatelná frakce aerosolu)
Remark	S - látka má senzibilizující účinek (s větou H317, H334), K - karcinogen kategorie 1A a 1B (s větou H350, H350i), T - toxická pro reprodukci kategorie 1A a 1B (s větou H360 včetně příslušných kódů).

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

cobalt dinitrate (10141-05-6)	
Regulatory reference	Nariadení vlády č. 361/2007 Sb. (Předpis 330/2023 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Cobalt, pulver, støv, røg og uorganiske forbindelser
OEL TWA	0,01 mg/m ³ beregnet som Co
Remark	K (betyder, at stoffet anses for at kunne være kræftfremkaldende)
Regulatory reference	BEK nr 291 af 19/03/2024
Estonia - Occupational Exposure Limits	
Local name	Koobalt ja anorgaanilised ühendid (arvutatud koobaltile)
OEL TWA	0,05 mg/m ³
Remark	S (Sensibiliseeriv aine)
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 02.04.2024, 13)
Finland - Occupational Exposure Limits	
Local name	Koboltti ja sen epäorgaaniset yhdisteet
HTP (OEL TWA)	0,02 mg/m ³ Co
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
Finland - Biological limit values	
Local name	Koboltti ja sen epäorgaaniset yhdisteet
BLV	130 nmol/l Parametri: Virtsan koboltti - Näytteenottoajankohta: Työvaiheen tai työvuoron päätyttyä työviikon tai altistumisjakson loputtua
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
Germany - Occupational Exposure Limits (TRGS 910)	
Local name	Cobalt und Cobaltverbindungen, als Carc.1A, Carc.1B eingestuft
Acceptable concentration (Weight conc.)	0,5 µg/m ³ (A)
Notes	b) Akzeptanzkonzentration assoziiert mit Risiko 4:10000
Tolerance concentration (Weight conc.)	5 µg/m ³ (A)
Tolerance concentration excess factor	8
Remark	(4) Die Konzentrationen beziehen sich auf den Elementgehalt des entsprechenden Metalls.; Siehe TRGS 561
Regulatory reference	TRGS 910
Greece - Occupational Exposure Limits	
Local name	Κοβάλτιο μεταλλικό (σκόνη και καπνοί)
OEL TWA	0,1 mg/m ³
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
Local name	KOBALT ÉS SZERVETLEN VEGYÜLETEI (Co-ra számítva)
AK (OEL TWA)	0,02 mg/m ³

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

cobalt dinitrate (10141-05-6)	
Remark	i (ingerlő anyag, amely izgatja a bőrt, nyálkahártyát, szemet vagy mindhármát), sz (Túlrézkénységet okozó (szenzibilizáló) tulajdonságú anyag. Az anyagra érzékeny egyéneken „túlrézkénységen” alapuló bőr-, légzőrendszeri, esetleg más szervet/szervrendszert károsító megbetegedést okozhat), BEM (biológiai expozíciós mutató); T (Azok az anyagok, amelyek egészségkárosító hatása TARTÓS expozíciót követően jelentkezik)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Hungary - Biological Exposure Indices	
Local name	Kobalt
BEI	0,01 mg/g creatinine Biológiai expozíciós (hatás) mutató: kobalt - Biológiai minta: vizeletben - Mintavétel ideje: m.v. (műszak végén) 0,019 µmol/mmol Creatinine Biológiai expozíciós (hatás) mutató: kobalt - Biológiai minta: vizeletben - Mintavétel ideje: m.v. (műszak végén)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	Cobalt & cobalt compounds (as Co)
OEL TWA	0,02 mg/m ³
Remark	Advisory OELV (Advisory Occupational Exposure Limit Values), Sens (In the workplace, respiratory or dermal exposures to sensitising agents may occur. Sensitisers may evoke respiratory or dermal reactions, e.g. asthma, rhinitis and allergic contact dermatitis. The “sens” notation alone does not distinguish between respiratory or dermal sensitisation. Chemical agents that are sensitisers present special problems in the workplace. Should an employee become sensitised, subsequent exposure may cause intense responses, even at low exposure concentrations well below the OELV. Exposure should be eliminated or significantly reduced through control measures such as engineering and process controls and use of personal protective equipment (PPE)), Carc.1B (Substances presumed to have carcinogenic potential for humans), Repr.1B (Substances which are presumed human reproductive toxicants)
Regulatory reference	Chemical Agents Code of Practice 2024
Ireland - Biological limit values	
Local name	Cobalt
BMGV	15 µg/l Parameter: cobalt - Medium: urine - Sampling time: End of shift at end of workweek - Notations: B (Background) 1 µg/l Parameter: cobalt - Medium: blood - Sampling time: End of shift at end of workweek - Notations: Sq (Semi-quantitative)
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
Latvia - Occupational Exposure Limits	
Local name	Kobalts
OEL TWA	0,5 mg/m ³ 0,5 mg/m ³
Remark	Carc. 1B; Muta. 2; Repr. 1B
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325 (Grozījumi Ministru kabineta 2024. gada 26. martā noteikumiem Nr. 191). Ministru kabineta 2008. gada 29. septembra noteikumi Nr. 803 (Grozījumi Ministru kabineta 2024. gada 26. martā noteikumiem Nr. 190).

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

cobalt dinitrate (10141-05-6)	
Netherlands - Occupational Exposure Limits	
Local name	Kobalt
TGG-8u (OEL TWA)	0,02 mg/m ³ (stof en rook) (als Co)
Regulatory reference	Arbeidsomstandighedenregeling 2024
Portugal - Occupational Exposure Limits	
Local name	Cobalto e compostos inorgânicos, expressos em Co
OEL TWA	0,02 mg/m ³
Remark	A3 (Agente carcinogénico confirmado nos animais de laboratório com relevância desconhecida no Homem); IBE (Índice biológico de exposição)
Regulatory reference	Norma Portuguesa NP 1796:2014
Portugal - Biological Exposure Indices	
Local name	Cobalto
BEI	15 µg/l Parâmetro: Cobalto - Meio: urina - Momento da amostragem: Fim do turno no fim da semana de trabalho - Notação: Vb (Valor basal) 1 µg/l Parâmetro: Cobalto - Meio: sangue - Momento da amostragem: Fim do turno no fim da semana de trabalho - Notação: Vb (Valor basal), Sq (Semi quantitativo)
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Cobalt
OEL TWA	0,05 mg/m ³
OEL STEL	0,1 mg/m ³
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 179/2024)
Romania - Biological limit values	
Local name	Cobalt
BLV	15 µg/l Indicatorul biologic: Cobalt - Material biologic: urină - Momentul recoltării: sfârşit de săptămână 1 µg/l Indicatorul biologic: Cobalt - Material biologic: sânge - Momentul recoltării: sfârşit de săptămână
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 179/2024)
Spain - Occupational Exposure Limits	
Local name	Cobalto elemental
VLA-ED (OEL TWA)	0,02 mg/m ³
Remark	VLB® (Agente químico que tiene Valor Límite Biológico), Sen (Sensibilizante).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2024. INSHT
Spain - Biological limit values	
Local name	Cobalto y compuestos inorgánicos excepto óxidos

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

cobalt dinitrate (10141-05-6)	
BLV	<p>15 µg/l Parámetro: Cobalto - Medio: Orina - Momento de muestreo: Final de la semana laboral - Notas: F (Fondo. El indicador está generalmente presente en cantidades detectables en personas no expuestas laboralmente. Estos niveles de fondo están considerados en el valor VLB)</p> <p>1 µg/l Parámetro: Cobalto - Medio: Sangre - Momento de muestreo: Final de la semana laboral - Notas: F (Fondo. El indicador está generalmente presente en cantidades detectables en personas no expuestas laboralmente. Estos niveles de fondo están considerados en el valor VLB), S (Significa que el indicador biológico es un indicador de exposición al agente químico en cuestión, pero la interpretación cuantitativa de su medida es ambigua (semicuantitativa). Estos indicadores biológicos deben utilizarse como una prueba de selección (screening) cuando no se pueda realizar una prueba cuantitativa o usarse como prueba de confirmación, si la prueba cuantitativa no es específica y el origen del determinante es dudoso)</p>
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2024. INSHT
Sweden - Occupational Exposure Limits	
Local name	Kobolt, och oorg. föreningar (som Co)
NGV (OEL TWA)	0,02 mg/m ³ inhalerbar fraktion
Remark	<p>C (Ämnet är cancerframkallande. Risk för cancer finns även vid annan exponering än via inandning. För vissa cancerframkallande ämnen som inte har gränsvärden gäller förbud eller tillståndskrav enligt föreskrifterna om kemiska arbetsmiljörisker); H (Ämnet kan lätt upptas genom huden. Det föreskrivna gränsvärdet bedöms ge tillräckligt skydd endast under förutsättning att huden är skyddad mot exponering för ämnet ifråga); S (Ämnet är sensibiliserande. Sensibiliserande ämnen kan ge allergi eller annan överkänslighet. Överkänslighetsbesvären drabbar främst huden eller andningsorganen. Överkänslighet innebär att man reagerar vid kontakt med ämnen som normalt inte ger besvär. Allergi är en undergrupp av överkänslighet som orsakas av reaktioner i kroppens immunsystem. Särskilt låga gränsvärden har fastställts för ämnen med mer uttalat luftvägssensibiliserande egenskaper. Några ämnen med starkt sensibiliserande egenskaper får endast hanteras efter tillstånd från Arbetsmiljöverket, se föreskrifterna om kemiska arbetsmiljörisker. Dessa ämnen har inga gränsvärden men i vissa fall riktvärden); 3 (Med inhalerbar fraktion menas den mängd partiklar, av totalmängden partiklar i luften, som man inandas genom näsa och mun)</p>
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	Cobalt
WEL TWA (OEL TWA)	0,1 mg/m ³ and Cobalt compounds (as Co)
Remark	Carc (cobalt dichloride and sulphate)(Capable of causing cancer and/or heritable genetic damage), Sen (Capable of causing occupational asthma)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Iceland - Occupational Exposure Limits	
Local name	Kóbalt, ryk, reykur og ólífræn sambönd sem Co
OEL TWA	0,02 mg/m ³
Remark	O (efnið er ofnæmisvaldandi)
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
Switzerland - Occupational Exposure Limits	
Local name	Cobalt et ses composés / Cobalt und seine Verbindungen [Kobalt]
MAK (OEL TWA)	0,05 mg/m ³ (i) / (e)

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

cobalt dinitrate (10141-05-6)	
Notation	R, S, C1 _B , M2, R1 _B , B / H, S, C1 _B , M2, R1 _B , B
Remark	HSE, NIOSH, BG. Exprimé en Co. / HSE, NIOSH, BG. Als Co berechnet.
Regulatory reference	www.suva.ch, 01.01.2024
Switzerland - BAT	
Local name	Cobalt et ses composés / Cobalt und seine Verbindungen
BAT	30 µg/l (509 nmol/l; Paramètre biologique: Cobalt; Substrat d'examen: Urine; Moment du prélèvement: Fin de l'exposition, de la période de travail.) / (509 nmol/l; Biologischer Parameter: Cobalt; Untersuchungsmaterial: Urin; Probenahmezeitpunkt: Expositionsende, bzw. Schichtende.)
Regulatory reference	Ordonnance 832.30 (OPA), article 50 al. 3, www.suva.ch/valeurs-limites / Verordnung 832.30 (VUV), Art. 50 Abs. 3, www.suva.ch/grenzwerte
USA - ACGIH - Occupational Exposure Limits	
Local name	Cobalt and inorganic compounds, as Co
ACGIH OEL TWA	0,02 mg/m ³ (I - Inhalable particulate matter)
Remark (ACGIH)	TLV® Basis: Pulm func changes. Notations: DSEN; RSEN; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2024
USA - ACGIH - Biological Exposure Indices	
Local name	Cobalt and inorganic compounds
BEI	15 µg/l Parameter: Cobalt - Medium: urine - Sampling time: End of shift at end of workweek - Notations: Ns
Regulatory reference	ACGIH 2024
thallium nitrate (10102-45-1)	
Austria - Occupational Exposure Limits	
Local name	Thalliumverbindungen lösliche
MAK (OEL TWA)	0,1 mg/m ³ (als TI berechnet, E)
MAK (OEL STEL)	1 mg/m ³ (als TI berechnet, E, 1x 30(Miw) min)
Regulatory reference	BGBl. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	Thallium (et composés) (en TI) # Thallium (en verbindingen) (als TI)
OEL TWA	0,02 mg/m ³
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
Bulgaria - Occupational Exposure Limits	
Local name	Талий
OEL TWA	0,05 mg/m ³ и неговите съединения (като талий)

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; Tl in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

thallium nitrate (10102-45-1)	
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 28 от 2024 г., в сила от 05.04.2024 г.)
Czech Republic - Occupational Exposure Limits	
Local name	Thallium
PEL (OEL TWA)	0,1 mg/m ³
NPK-P (OEL C)	0,5 mg/m ³
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 330/2023 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Thalliumforbindelser, opløselige
OEL TWA	0,1 mg/m ³ beregnet som Tl
Remark	H (betyder, at stoffet kan optages gennem huden)
Regulatory reference	BEK nr 291 af 19/03/2024
Finland - Occupational Exposure Limits	
Local name	Tallium
HTP (OEL TWA)	0,1 mg/m ³
Remark	Iho
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
France - Occupational Exposure Limits	
Local name	Thallium
VME (OEL TWA)	0,1 mg/m ³
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 6443, 2022; Outil65)
Ireland - Occupational Exposure Limits	
Local name	Thallium and compounds (as Tl)
OEL TWA	0,02 mg/m ³
Remark	Advisory OELV (Advisory Occupational Exposure Limit Values), Skin (Substances which have the capacity to penetrate intact skin when they come in contact with it and be absorbed into the body. A substantial contribution to the total body burden via dermal exposure is possible)
Regulatory reference	Chemical Agents Code of Practice 2024
Poland - Occupational Exposure Limits	
Local name	Tal i jego związki w przeliczeniu na Tl
NDS (OEL TWA)	0,1 mg/m ³
NDSch (OEL STEL)	0,3 mg/m ³
Regulatory reference	Dz. U. 2024 poz. 1017 wraz z późn. zm.
Portugal - Occupational Exposure Limits	
Local name	Tálio, e compostos solúveis, expressos em Tl
OEL TWA	0,02 mg/m ³ I (Fração inalável)
Remark	P (Toxicidade percutânea)

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

thallium nitrate (10102-45-1)	
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Thaliu (compuși solubili)
OEL STEL	0,05 mg/m ³
Spain - Occupational Exposure Limits	
Local name	Talio
VLA-ED (OEL TWA)	0,1 mg/m ³ elemental 0,1 mg/m ³ Compuestos solubles de talio, como TI
Remark	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante. Para más información véase el Apartado 5 de este documento), c (Los términos "soluble" e "insoluble" se entienden con referencia al agua).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2024. INSHT
United Kingdom - Occupational Exposure Limits	
Local name	Thallium
WEL TWA (OEL TWA)	0,1 mg/m ³ soluble compounds (as TI)
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Iceland - Occupational Exposure Limits	
Local name	Þallíumsambönd, uppleysanleg, sem TI
OEL TWA	0,1 mg/m ³
Remark	H
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
Norway - Occupational Exposure Limits	
Local name	Thallium og løselige thalliumforb. (beregnet som TI)
Grenseverdi (OEL TWA)	0,02 mg/m ³
Remark	H: Kjemikalier som kan tas opp gjennom huden.
Regulatory reference	FOR-2024-04-05-581
Switzerland - Occupational Exposure Limits	
Local name	Thallium, composés solubles / Thalliumverbindungen, löslich
MAK (OEL TWA)	0,1 mg/m ³ (i) / (e)
Notation	R / H
Remark	NIOSH, OSHA
Regulatory reference	www.suva.ch, 01.01.2024
USA - ACGIH - Occupational Exposure Limits	
Local name	Thallium and compounds, as TI
ACGIH OEL TWA	0,02 mg/m ³ (I - Inhalable particulate matter)

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

thallium nitrate (10102-45-1)	
Remark (ACGIH)	TLV® Basis: GI dam; peripheral neuropathy. Notations: Skin
Regulatory reference	ACGIH 2024

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure. Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the protective equipment.

Personal protective equipment symbol(s):

Eye and face protection

Eye protection:

Safety glasses

Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Not available
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Non flammable.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Miscible with water.

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 1,06
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

metals.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

nitric acid (7697-37-2)	
LC50 Inhalation - Rat	> 2,65 mg/L air
hydrofluoric Acid (7664-39-3)	
LD50 dermal rabbit	≤ 50 mg/kg
lithium nitrate (7790-69-4)	
LD50 oral rat	1426 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight
LC50 Inhalation - Rat	> 5,93 mg/l/4h
yttrium trinitrate, hexahydrate (13494-98-9)	
LD50 oral rat	1650 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

cobalt dinitrate (10141-05-6)	
LD50 oral rat	691 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight
thallium nitrate (10102-45-1)	
LD50 oral rat	15 mg/kg
Skin corrosion/irritation	: Causes severe skin burns.
nitric acid (7697-37-2)	
pH	< 1
hydrofluoric Acid (7664-39-3)	
pH	< 1
yttrium trinitrate, hexahydrate (13494-98-9)	
pH	1,81 (20 °C)
cobalt dinitrate (10141-05-6)	
pH	4
Serious eye damage/irritation	: Causes serious eye damage.
nitric acid (7697-37-2)	
pH	< 1
hydrofluoric Acid (7664-39-3)	
pH	< 1
yttrium trinitrate, hexahydrate (13494-98-9)	
pH	1,81 (20 °C)
cobalt dinitrate (10141-05-6)	
pH	4
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
cobalt dinitrate (10141-05-6)	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
nitric acid (7697-37-2)	
NOAEL (oral, rat, 90 days)	1500 mg/kg bodyweight
NOAEC (inhalation, rat, gas, 90 days)	2,15 ppm
yttrium trinitrate, hexahydrate (13494-98-9)	
NOAEL (oral, rat, 90 days)	≥ 1000 mg/kg bodyweight
cobalt dinitrate (10141-05-6)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0,31 mg/L air
NOAEL (oral, rat, 90 days)	3 mg/kg bodyweight

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

thallium nitrate (10102-45-1)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

nitric acid (7697-37-2)	
Viscosity, kinematic	0,595 mm ² /s

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Not classified

nitric acid (7697-37-2)	
EC50 - Crustacea [1]	180 mg/l Daphnia magna (Water flea)
Threshold limit - Algae [1]	> 19 mg/l

hydrofluoric Acid (7664-39-3)	
EC50 - Crustacea [1]	270 mg/l Daphnia magna (Water flea)
NOEC (chronic)	14,1 mg/l Daphnia magna (Water flea)
NOEC chronic fish	4 mg/l Oncorhynchus mykiss (Rainbow trout)

lithium nitrate (7790-69-4)	
LC50 - Fish [1]	158 mg/l Oncorhynchus mykiss (Rainbow trout)
EC50 - Crustacea [1]	249 mg/l Daphnia magna (Water flea)
LOEC (chronic)	2,53 mg/l Daphnia magna (Water flea)
NOEC (chronic)	1,7 mg/l Daphnia magna (Water flea)

yttrium trinitrate, hexahydrate (13494-98-9)	
LC50 - Fish [1]	0,62 mg/l Oncorhynchus mykiss (Rainbow trout)

cobalt dinitrate (10141-05-6)	
LC50 - Fish [1]	1,5 mg/l (mg Co/L) Oncorhynchus mykiss (Rainbow trout)
EC50 - Crustacea [1]	5,89 mg/l Daphnia magna (Water flea)

thallium nitrate (10102-45-1)	
LC50 - Fish [1]	180 mg/l
EC50 - Crustacea [1]	1,6 mg/l

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.2. Persistence and degradability

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564	
Persistence and degradability	Rapidly degradable
nitric acid (7697-37-2)	
Persistence and degradability	Rapidly degradable
hydrofluoric Acid (7664-39-3)	
Persistence and degradability	Rapidly degradable
lithium nitrate (7790-69-4)	
Persistence and degradability	Rapidly degradable
yttrium trinitrate, hexahydrate (13494-98-9)	
Persistence and degradability	Rapidly degradable
cobalt dinitrate (10141-05-6)	
Persistence and degradability	Rapidly degradable
thallium nitrate (10102-45-1)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

nitric acid (7697-37-2)	
Partition coefficient n-octanol/water (Log Pow)	-2,3
hydrofluoric Acid (7664-39-3)	
Partition coefficient n-octanol/water (Log Pow)	-1,4
lithium nitrate (7790-69-4)	
Partition coefficient n-octanol/water (Log Pow)	-0,79
thallium nitrate (10102-45-1)	
Partition coefficient n-octanol/water (Log Pow)	0,21

12.4. Mobility in soil

lithium nitrate (7790-69-4)	
Mobility in soil	13,22

12.5. Results of PBT and vPvB assessment

Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	nitric acid (7697-37-2), hydrofluoric Acid (7664-39-3), lithium nitrate (7790-69-4) ⁽¹⁾ , yttrium trinitrate, hexahydrate (13494-98-9) ⁽¹⁾ , cobalt dinitrate (10141-05-6) ⁽¹⁾ , thallium nitrate (10102-45-1) ⁽¹⁾
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	nitric acid (7697-37-2), hydrofluoric Acid (7664-39-3), lithium nitrate (7790-69-4) ⁽¹⁾ , yttrium trinitrate, hexahydrate (13494-98-9) ⁽¹⁾ , cobalt dinitrate (10141-05-6) ⁽¹⁾ , thallium nitrate (10102-45-1) ⁽¹⁾

⁽¹⁾ Substance(s) in concentration below 0.1 % and displayed on a voluntary basis

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available






SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 3264	UN 3264	UN 3264	UN 3264	UN 3264
14.2. UN proper shipping name				
CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid ; hydrofluoric Acid)	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid ; hydrofluoric Acid)	Corrosive liquid, acidic, inorganic, n.o.s. (nitric acid ; hydrofluoric Acid)	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid ; hydrofluoric Acid)	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid ; hydrofluoric Acid)
Transport document description				
UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid ; hydrofluoric Acid), 8, II, (E)	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid ; hydrofluoric Acid), 8, II	UN 3264 Corrosive liquid, acidic, inorganic, n.o.s. (nitric acid ; hydrofluoric Acid), 8, II	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid ; hydrofluoric Acid), 8, II	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid ; hydrofluoric Acid), 8, II
14.3. Transport hazard class(es)				
8	8	8	8	8
				
14.4. Packing group				
II	II	II	II	II
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-A EmS-No. (Spillage): S-B	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564


Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: C1
Special provisions (ADR)	: 274
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02
Mixed packing provisions (ADR)	: MP15
Portable tank and bulk container instructions (ADR)	: T11
Portable tank and bulk container special provisions (ADR)	: TP2, TP27
Tank code (ADR)	: L4BN
Vehicle for tank carriage	: AT
Transport category (ADR)	: 2
Hazard identification number (Kemler No.)	: 80
Orange plates	:



Tunnel restriction code (ADR)	: E
EAC code	: 2X
APP code	: B

Transport by sea

Special provisions (IMDG)	: 274
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T11
Tank special provisions (IMDG)	: TP2, TP27
Stowage category (IMDG)	: B
Stowage and handling (IMDG)	: SW2

Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y840
PCA limited quantity max net quantity (IATA)	: 0.5L
PCA packing instructions (IATA)	: 851
PCA max net quantity (IATA)	: 1L
CAO packing instructions (IATA)	: 855
CAO max net quantity (IATA)	: 30L
Special provisions (IATA)	: A3
ERG code (IATA)	: 8L

Inland waterway transport

Classification code (ADN)	: C1
Special provisions (ADN)	: 274
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E2
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EP
Number of blue cones/lights (ADN)	: 0

Rail transport

Classification code (RID)	: C1
Special provisions (RID)	: 274
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P001, IBC02

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Mixed packing provisions (RID)	: MP15
Portable tank and bulk container instructions (RID)	: T11
Portable tank and bulk container special provisions (RID)	: TP2, TP27
Tank codes for RID tanks (RID)	: L4BN
Transport category (RID)	: 2
Colis express (express parcels) (RID)	: CE6
Hazard identification number (RID)	: 80

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	nitric acid	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564 ; nitric acid ; hydrofluoric Acid	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains substance(s) listed on the REACH Candidate List < 0.1% or SCL: Cobalt(II) dinitrate (EC 233-402-1, CAS 10141-05-6).

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items: Hydrogen fluoride (7664-39-3).

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX I RESTRICTED EXPLOSIVES PRECURSORS

List of substances which are not to be made available to, or introduced, possessed or used by, members of the general public, whether on their own or in mixtures or substances that include those substances, unless the concentration is equal to or lower than the limit values set out in column 2, and for which suspicious transactions and significant disappearances and thefts are to be reported within 24 hours.

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	CAS-No.	Limit value	Upper limit value for licensing under Article 5(3)	Combined Nomenclature (CN) code for a separate chemically defined compound meeting the requirements of Note 1 to Chapter 28 or 29 of the CN, respectively	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Nitric acid	7697-37-2	3 % w/w	10% w/w	ex 2808 00 00	ex 3824 99 96

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

National regulations

France

Occupational diseases	
Code	Description
RG 32	Occupational disorders caused by fluoride, hydrofluoric acid and its mineral salts
RG 70	Occupational diseases caused by cobalt and its compounds
RG 70 BIS	Respiratory disorders due to sintered or fused metal carbide dust containing cobalt
RG 70 TER	Primary broncho-pulmonary cancer caused by inhalation of cobalt dust associated with tungsten carbide prior to sintering

Germany

VOC ordinance (ChemVOCFarbV) :

Water hazard class (WGK) : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).

Hazardous Incident Ordinance (12. BImSchV) : Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : B(4) - low hazard for aquatic organisms

SZW-lijst van kankerverwekkende stoffen : lithium nitrate, cobalt dinitrate are listed

SZW-lijst van mutagene stoffen : lithium nitrate is listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : cobalt dinitrate is listed

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Poland

Polish National Regulations

: Act of 25 February 2011 on chemical substances and their mixtures (J. o L. No. 63, item 322 as amended; consolidated text J. o L. 2019, item 1225).
Act of 14 December 2012 on waste (J. o L. 2013, item 322 as amended; consolidated text J. o L. 2020, item 797).
The announcement of Marshal of the Sejm of the Republic of Poland dated 19 October 2016 concerning the consolidated text announcement of the decree on the management of packaging and packaging waste (J. o L. 2016, item 1863 as amended).
Decree of the Minister of Environment of 14 December 2014 on the catalogue of waste (J. o L. 2014, item 1923).
Act of 19 August 2011 on the Carriage of Dangerous Goods (J. o L. 2011 No. 227, item 1367 as amended; consolidated text J. o L. 2020, item 154).
Regulation of the Minister of Family, Labour and Social Policy of 12 June 2018 on the highest permissible concentration and intensity of noxious agents for health at work environment (J. o L. item 1286 as amended).
The announcement of Minister of Health dated 9 September 2016 concerning the consolidated text announcement of the decree of the Minister of Health of 30 December 2004 on health and safety at work related to exposure to chemical agents at work (J. o L. of 16 September 2016, item 1488)
Regulation of the Minister of Health of 2 February 2011 on tests and measurements of the noxious agents for health at work environment (J. o L. No. 33, item 166 as amended).
Regulation of the Minister of Environment of 9 December 2003 on particularly hazardous substances to the environment (J. o L. No. 217, item 2141).
ADR Agreement: Government Statement of 13 March 2023 on the entry into force of amendments to Annexes A and B to the Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), signed in Geneva on 30 September 1957 (J. o. L. 2023, item 891)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes		
Section	Changed item	Comments
4.1	First-aid measures for first aider	Added
4.2	Symptoms/effects after inhalation	Added
5.1	Unsuitable extinguishing media	Added
5.2	Fire hazard	Added
5.2	Explosion hazard	Added
5.3	Firefighting instructions	Added
6.1	Emergency procedures	Added
6.1	Protective equipment	Added
6.1	General measures	Added
6.3	For containment	Added
7.1	Additional hazards when processed	Added
7.2	Technical measures	Added
7.2	Packaging materials	Added
7.2	Storage conditions	Modified

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes		
Section	Changed item	Comments
13.1	Sewage disposal recommendations	Added
13.1	Additional information	Added
13.1	Regional waste regulation	Added
13.1	Product/Packaging disposal recommendations	Modified
15.1	REACH Annex XVII	Modified
16	Abbreviations and acronyms	Modified

Abbreviations and acronyms:	
ACGIH	American Conference of Government Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
COD	Chemical oxygen demand (COD)
CSA	Chemical safety assessment
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
ED	Endocrine disruptor
EN	European Standard
EWC	European waste catalogue
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
Log Kow	Partition coefficient n-octanol/water (Log Kow)
Log Pow	Partition coefficient n-octanol/water (Log Pow)
MAK	maximum workplace concentration
NOAEC	No-Observed Adverse Effect Concentration

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:

NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
N.O.S.	Not Otherwise Specified
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
OSHA	Occupational Safety Health Administration
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
PPE	Personal protection equipment
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TF	Technical function
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
TWA	Time Weighted Average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative
UFI	Unique Formula Identifier

Full text of H- and EUH-statements:

Acute Tox. 1 (Dermal)	Acute toxicity (dermal), Category 1
Acute Tox. 1 (Inhalation)	Acute toxicity (inhal.), Category 1
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 2 (Oral)	Acute toxicity (oral), Category 2
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Carc. 1B	Carcinogenicity (inhalation) Category 1B
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Met. Corr. 1	Corrosive to metals, Category 1
Muta. 2	Germ cell mutagenicity, Category 2
Ox. Liq. 2	Oxidising Liquids, Category 2
Ox. Liq. 3	Oxidising Liquids, Category 3
Ox. Sol. 2	Oxidising Solids, Category 2
Ox. Sol. 3	Oxidising Solids, Category 3

ICP-MS Stock Tuning Solution- 5 components; 10mg/l each of Li ; Y ; Ce ; Co ; TI in HNO3 5% /tr HF Equivalent to Agilent Ref: 5188-6564

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Repr. 1B	Reproductive toxicity, Category 1B
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT RE Not classified	Specific target organ toxicity (repeated exposure) Not classified
H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H300	Fatal if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H341	Suspected of causing genetic defects.
H350i	May cause cancer by inhalation.
H360FD	May damage fertility. May damage the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Met. Corr. 1	H290	On basis of test data
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.