



Instrument Calibration Standard 1 - 4 components; 5000mg/l each of Ca ; K ; Mg ; Na in HNO3 5% Equivalent to Perkin Elmer Ref: N9300218

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 09/10/2016

Revision date: 09/10/2016

Version: 1.1

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Name : Instrument Calibration Standard 1 - 4 components; 5000mg/l each of Ca ; K ; Mg ; Na in HNO3 5% Equivalent to Perkin Elmer Ref: N9300218
Product code : EQ0124

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Certified reference material for laboratory use

1.3. Details of the supplier of the safety data sheet

Spectracer UK Ltd.

Second Floor,
27 Gloucester Place,
London,
W1U 8HU,
United Kingdom.

Tel: +44 (0) 207 193 9114

Fax: +44 (0) 203 432 4686

Email: contact@spectracer.co.uk

Web: www.spectracer.com

1.4. Emergency telephone number

Emergency number : Tel: +44(0)1933445260 Option 1. Language: English only.
For Chemical Emergencies Only
Llewellyn (Safety Advisors) Europe Ltd

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Corrosive to metals H290

Category 1

Skin corrosion/irritation H314

Category 1A

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS05

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H290 - May be corrosive to metals
H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS-US) :

P234 - Keep only in original container
P260 - Do not breathe dust/fume/gas/mist/vapors/spray
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

Instrument Calibration Standard 1 - 4 components; 5000mg/l each of Ca ; K ; Mg ; Na in HNO3 5% Equivalent to Perkin Elmer Ref: N9300218

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a poison center/doctor/...
P363 - Wash contaminated clothing before reuse
P390 - Absorb spillage to prevent material damage
P405 - Store locked up
P501 - Dispose of contents/container to ..

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
nitric acid	(CAS No) 7697-37-2	5 - 15	Ox. Liq. 3, H272 Met. Corr. 1, H290 Skin Corr. 1A, H314
magnesium nitrate	(CAS No) 10377-60-3	1 - 5	Eye Irrit. 2A, H319
calcium nitrate	(CAS No) 10124-37-5	1 - 5	Eye Irrit. 2A, H319
sodium nitrate	(CAS No) 7631-99-4	1 - 5	Acute Tox. 4 (Oral), H302 Eye Irrit. 2A, H319

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after skin contact : Burns.
Symptoms/injuries after eye contact : Serious damage to eyes.
Symptoms/injuries after ingestion : Burns.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

Instrument Calibration Standard 1 - 4 components; 5000mg/l each of Ca ; K ; Mg ; Na in HNO3 5% Equivalent to Perkin Elmer Ref: N9300218

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in corrosive resistant container with a resistant inner liner. Keep only in original container. Store locked up. Store in a well-ventilated place. Keep cool.

Incompatible materials : Metals.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

nitric acid (7697-37-2)		
ACGIH	ACGIH TWA (ppm)	2 ppm
ACGIH	ACGIH STEL (ppm)	4 ppm
ACGIH	Remark (ACGIH)	URT & eye irr; dental erosion
OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	2 ppm
calcium nitrate (10124-37-5)		
Not applicable		
magnesium nitrate (10377-60-3)		
Not applicable		
sodium nitrate (7631-99-4)		
Not applicable		

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Instrument Calibration Standard 1 - 4 components; 5000mg/l each of Ca ; K ; Mg ; Na in HNO3 5% Equivalent to Perkin Elmer Ref: N9300218

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal protective equipment : Avoid all unnecessary exposure. Gloves. Safety glasses. Protective clothing.



Hand protection : Protective gloves.
Eye protection : Safety glasses.
Skin and body protection : Wear suitable protective clothing.
Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Mixture contains one or more component(s) which have the following colour(s): colorless to yellow On exposure to light: red-brown Colorless Colourless-white Colourless to white White
Odor : There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure.
Mixture contains one or more component(s) which have the following odour(s): irritating/pungent odor asphyxiating odor Odorless
Odor threshold : No data available
pH : No data available
Melting point : Not applicable
Freezing point : No data available
Boiling point : No data available
Flash point : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : Not applicable.
Vapor pressure : No data available
Relative vapor density at 20 °C : No data available
Relative density : 1.06
Solubility : Miscible with water.
Log Pow : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosion limits : No data available
Explosive properties : No data available
Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

Instrument Calibration Standard 1 - 4 components; 5000mg/l each of Ca ; K ; Mg ; Na in HNO3 5% Equivalent to Perkin Elmer Ref: N9300218

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

metals.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

magnesium nitrate (10377-60-3)	
LD50 oral rat	> 2000 mg/kg body weight (Rat; OECD 423: Acute Oral Toxicity – Acute Toxic Class Method; Experimental value)
LD50 dermal rat	> 5000 mg/kg body weight (Rat; Read-across; OECD 402: Acute Dermal Toxicity)
sodium nitrate (7631-99-4)	
LD50 oral rat	1270 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value; 3430 mg/kg bodyweight; Rat)
LD50 dermal rat	> 5000 mg/kg body weight (Rat; Read-across; OECD 402: Acute Dermal Toxicity)
ATE US (oral)	1270.000 mg/kg body weight

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Symptoms/injuries after skin contact : Burns.

Symptoms/injuries after eye contact : Serious damage to eyes.

Symptoms/injuries after ingestion : Burns.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

nitric acid (7697-37-2)	
EC50 Daphnia 1	180 mg/l (EC50; 48 h)
LC50 fish 2	72 ppm (LC50; 96 h)
Threshold limit algae 1	> 19 mg/l (EC0)
calcium nitrate (10124-37-5)	
EC50 Daphnia 1	2355 mg/l (LC50; 120 h)
LC50 fish 2	10000 mg/l (LC50; 96 h; Lepomis macrochirus)

Instrument Calibration Standard 1 - 4 components; 5000mg/l each of Ca ; K ; Mg ; Na in HNO3 5% Equivalent to Perkin Elmer Ref: N9300218

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

magnesium nitrate (10377-60-3)	
LC50 fish 1	1378 mg/l (LC50; Equivalent or similar to OECD 203; 96 h; Poecilia reticulata; Static system; Fresh water; Read-across)
EC50 Daphnia 1	490 mg/l (EC50; 48 h; Daphnia magna)
Threshold limit algae 1	> 1700 mg/l (EC50; 10 days; Nitzschia closterium)
sodium nitrate (7631-99-4)	
EC50 other aquatic organisms 1	> 1700 mg/l (10 days; Algae; EC50; Other)
LC50 fish 2	4650 mg/l (LC50; Other; 96 h; Salmo gairdneri; Static system; Fresh water; Experimental value)
EC50 Daphnia 2	7240 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 24 h; Daphnia magna; Static system; Fresh water; Experimental value)

12.2. Persistence and degradability

nitric acid (7697-37-2)	
Persistence and degradability	Biodegradability: Not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

calcium nitrate (10124-37-5)	
Persistence and degradability	Biodegradable in soil.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

magnesium nitrate (10377-60-3)	
Persistence and degradability	Biodegradability: Not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

sodium nitrate (7631-99-4)	
Persistence and degradability	Biodegradability: Not applicable. No (test)data available on mobility of the substance.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

12.3. Bioaccumulative potential

nitric acid (7697-37-2)	
BCF fish 1	<= 1 (BCF)
Log Pow	-2.3 (OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method)
Bioaccumulative potential	Bioaccumulation: Not applicable.

calcium nitrate (10124-37-5)	
Bioaccumulative potential	Not bioaccumulative.

magnesium nitrate (10377-60-3)	
Log Pow	-0.61 (Estimated value)
Bioaccumulative potential	Bioaccumulation: Not applicable.

sodium nitrate (7631-99-4)	
Log Pow	-3.8
Bioaccumulative potential	Bioaccumulation: Not applicable.

Instrument Calibration Standard 1 - 4 components; 5000mg/l each of Ca ; K ; Mg ; Na in HNO3 5% Equivalent to Perkin Elmer Ref: N9300218

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known effects from this product.
GWPmix comment : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN3264 Corrosive liquid, acidic, inorganic, n.o.s. (CONTAINS ; nitric acid), 8, II

UN-No.(DOT) : UN3264

Proper Shipping Name (DOT) : Corrosive liquid, acidic, inorganic, n.o.s.
CONTAINS ; nitric acid

Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Packing group (DOT) : II - Medium Danger

Hazard labels (DOT) : 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102) : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized

T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 1 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 30 L

Instrument Calibration Standard 1 - 4 components; 5000mg/l each of Ca ; K ; Mg ; Na in HNO3 5% Equivalent to Perkin Elmer Ref: N9300218

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
Emergency Response Guide (ERG) Number	: 154
Other information	: No supplementary information available.

TDG

Transport document description	: UN3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (CONTAINS ; nitric acid), 8, II
UN-No. (TDG)	: UN3264
Proper Shipping Name (TDG)	: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
TDG Primary Hazard Classes	: 8 - Class 8 - Corrosives
Packing group	: II - Medium Danger
TDG Special Provisions	: 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the hazard or hazards posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A) of Part 3 (Documentation). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4 (Dangerous Goods Safety Marks). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a)UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; (b)UN1851, MEDICINE, LIQUID, TOXIC, N.O.S; (c)UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; (d)UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or (e)UN3249, MEDICINE, SOLID, TOXIC, N.O.S. An example in Canada is the "Food and Drugs Act". (3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment: (a)UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b)UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS. SOR/2014-306
Explosive Limit and Limited Quantity Index	: 1 L
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 1 L

Transport by sea

UN-No. (IMDG)	: 3264
Proper Shipping Name (IMDG)	: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
Class (IMDG)	: 8 - Corrosive substances
Packing group (IMDG)	: II - substances presenting medium danger
Limited quantities (IMDG)	: 1 L

Air transport

UN-No. (IATA)	: 3264
Proper Shipping Name (IATA)	: Corrosive liquid, acidic, inorganic, n.o.s.
Class (IATA)	: 8 - Corrosives
Packing group (IATA)	: II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Instrument Calibration Standard 1 - 4 components; 5000mg/l each of Ca ; K ; Mg ; Na in HNO3 5% Equivalent to Perkin Elmer Ref: N9300218

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

nitric acid (7697-37-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	1000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb
calcium nitrate (10124-37-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
magnesium nitrate (10377-60-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
sodium nitrate (7631-99-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information

Revision date : 09/10/2016


Full text of H-phrases:

H272	May intensify fire; oxidizer
H290	May be corrosive to metals
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H319	Causes serious eye irritation

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 0 - Materials that will not burn.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection : C

C - Safety glasses, Gloves, Synthetic apron

Instrument Calibration Standard 1 - 4 components; 5000mg/l each of Ca ; K ; Mg ; Na in HNO3 5% Equivalent to Perkin Elmer Ref: N9300218

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.