

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SDS Reference Number: S107

Issue date: 18/10/2015 Revision date: 08/01/2025 Supersedes version of: 30/03/2023 Version: 1.4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : ICP Standard Solution
Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%
Product code : S107

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Professional use
Use of the substance/mixture : Reference material
Function or use category : Laboratory chemicals

1.3. Details of the supplier of the safety data sheet

Spectracer UK Ltd.

20 Seymour Mews,
London,
W1H 6BQ,
United Kingdom.

Tel: +44 (0) 207 193 9114

Fax: +44 (0) 203 432 4686

Email: contact@spectracer.com

Web: www.spectracer.com

1.4. Emergency telephone number

Country/Area	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	: +353 1 8379964	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital Msida MSD 2090 Msida	112 +356 2545 6508	
United Kingdom	National Poisons Information Service (NHS Direct)	http://www.npis.org	111 (England & Wales only) or 112 (EU) or 08454 24 24 24 (Scotland)	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4 H302
Acute toxicity (dermal), Category 3 H311
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317
Carcinogenicity, Category 1B H350
Specific target organ toxicity – Repeated exposure, Category 2 H373

Full text of H- and EUH-statements: see section 16

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Adverse physicochemical, human health and environmental effects

May cause cancer. May cause damage to organs through prolonged or repeated exposure. Toxic in contact with skin. Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS06

GHS07

GHS08

Signal word (CLP)

: Danger

Contains

: beryllium nitrate; nitric acid; hydrofluoric Acid

Hazard statements (CLP)

: H302 - Harmful if swallowed.
H311 - Toxic in contact with skin.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H350 - May cause cancer.
H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements (CLP)

: P201 - Obtain special instructions before use.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313 - IF exposed or concerned: Get medical advice/attention.
P312 - Call a POISON CENTRE or doctor if you feel unwell.
P314 - Get medical advice/attention if you feel unwell.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.
P362+P364 - Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	beryllium nitrate (13597-99-4), nitric acid (7697-37-2), hydrofluoric Acid (7664-39-3)
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	beryllium nitrate (13597-99-4), nitric acid (7697-37-2), hydrofluoric Acid (7664-39-3)

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
nitric acid substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PT, RO, SE, SI, SK, AL, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 7697-37-2 EC-No.: 231-714-2 EC Index-No.: 007-004-00-1 REACH-no: 01-2119487297-23-XXXX	2	Ox. Liq. 3, H272 Met. Corr. 1, H290 Acute Tox. 1 (Inhalation), H330 Skin Corr. 1A, H314 Eye Dam. 1, H318
beryllium nitrate substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, GB, HR, HU, IE, PL, PT, RO, SE, SI, IS, MK); substance with a Community workplace exposure limit	CAS-No.: 13597-99-4 EC-No.: 237-062-5 EC Index-No.: 004-002-00-2	1-2	Ox. Sol. 2, H272 Acute Tox. 3 (Oral), H301 Acute Tox. 2 (Inhalation), H330 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Carc. 1B, H350i STOT SE 3, H335 STOT RE 1, H372 Aquatic Chronic 2, H411
hydrofluoric Acid substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, AL, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 7664-39-3 EC-No.: 231-634-8 EC Index-No.: 009-002-00-6 REACH-no: 01-2119458860-33-XXXX	0.5	Met. Corr. 1, H290 Acute Tox. 2 (Oral), H300 Acute Tox. 1 (Dermal), H310 Acute Tox. 2 (Inhalation), H330 Skin Corr. 1A, H314

Specific concentration limits:

Name	Product identifier	Specific concentration limits (%)
nitric acid	CAS-No.: 7697-37-2 EC-No.: 231-714-2 EC Index-No.: 007-004-00-1 REACH-no: 01-2119487297-23-XXXX	(5 ≤ C < 20) Skin Corr. 1B; H314 (20 ≤ C < 100) Skin Corr. 1A; H314 (65 ≤ C < 99) Ox. Liq. 3; H272 (99 ≤ C < 100) Ox. Liq. 2; H272
hydrofluoric Acid	CAS-No.: 7664-39-3 EC-No.: 231-634-8 EC Index-No.: 009-002-00-6 REACH-no: 01-2119458860-33-XXXX	(0.1 ≤ C < 1) Eye Irrit. 2; H319 (1 ≤ C < 7) Skin Corr. 1B; H314 (7 ≤ C < 100) Skin Corr. 1A; H314

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Call a poison center or a doctor if you feel unwell.
First-aid measures for first aider	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: Toxic in contact with skin. Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: Harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	---

For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Wear personal protective equipment. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing.
Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.
Storage conditions : Store locked up.
Packaging materials : Store always product in container of same material as original container.

Germany

Storage class (LGK, TRGS 510) : LGK 6.1D - Non-combustible substances of acute toxicity, category 3 / hazardous substances that are toxic or produce chronic effects

Joint storage table :

LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for : LGK 1, LGK 2A, LGK 4.1A, LGK 5.1A, LGK 5.1C, LGK 5.2, LGK 6.2, LGK 7
Joint storage with restrictions permitted for : LGK 3, LGK 4.1B, LGK 4.2, LGK 4.3, LGK 5.1B
Joint storage permitted for : LGK 2B, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK 10-13

Switzerland

Storage class (LK) : LK 6.1 - Toxic materials

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

beryllium nitrate (13597-99-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Beryllium
IOEL TWA	0.0002 mg/m ³ (BOEL. Inhalable fraction) 0.0006 mg/m ³ (Limit value until 11 July 2026)
	0.02 µg/m ³ (inhalable fraction)
IOEL STEL	0.2 µg/m ³ (inhalable fraction)
Remark	Dermal and respiratory sensitisation Sensitisation (dermal and respiratory). (Year of adoption 2017)
Regulatory reference	DIRECTIVE (EU) 2019/983 (amending Directive 2004/37/EC) SCOEL Recommendations
EU - Binding Occupational Exposure Limit (BOEL)	
Local name	Beryllium
BOEL TWA	0.0002 mg/m ³ (Inhalable fraction) 0.0006 mg/m ³ (Limit value until 11 July 2026)
Notes	Dermal and respiratory sensitisation (The substance can cause sensitisation of the skin and of the respiratory tract)
Regulatory reference	DIRECTIVE (EU) 2019/983 (amending Directive 2004/37/EC)
EU - Biological Limit Value (BLV)	
Local name	Beryllium
Regulatory reference	SCOEL List of recommended health-based BLVs and BGVs
Austria - Occupational Exposure Limits	
Local name	Beryllium und seine Verbindungen
MAK (OEL TWA)	0.00002 mg/m ³ (als Be berechnet, E)
MAK (OEL STEL)	0.0002 mg/m ³ (als Be berechnet, E, 4x 15(Miw) min)
TRK (OEL TWA)	0.0006 mg/m ³ (als Be berechnet, E)
TRK (OEL STEL)	0.0024 mg/m ³ (als Be berechnet, E, 4x 15(Miw) min)
Remark	Sah. Krebs erzeugend: III A2
Regulatory reference	BGBI. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	Béryllium et ses composés (en Be) # Beryllium en -verbindingen (als Be)
OEL TWA	0.002 mg/m ³
OEL STEL	0.01 mg/m ³
Remark	C: La mention C signifie que l'agent en question relève du champ d'application de l'arrêté royal du 2 décembre 1993 concernant la protection des travailleurs contre les risques liés à l'exposition à des agents cancérigènes et mutagènes au travail. # De vermelding C betekent dat het betrokken agens valt onder het toepassingsgebied van het koninklijk besluit van 2 december 1993 betreffende de bescherming van de werknemers tegen de risico's van blootstelling aan kankerverwekkende en mutagene agentia op het werk
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
Bulgaria - Occupational Exposure Limits	
Local name	Берилий

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

beryllium nitrate (13597-99-4)	
OEL TWA	0.002 mg/m ³ и съединения (като берилий)
Remark	Кожна и дихателна сенсibilизация (Веществото може да предизвика сенсibilизация на кожата и на дихателните пътища)
Regulatory reference	Наредба № 10 от 26.09.2003 г. за защита на работещите от рискове, свързани с експозиция на канцерогени и мутагени при работа (изм. и доп. ДВ. бр. 28 от 2 Април 2024г.)
Croatia - Occupational Exposure Limits	
Local name	Berilij
GVI (OEL TWA)	0.002 mg/m ³
Remark	T+ (vrlo otrovno); Karc. kat. 2 (tvori koje su vjerojatno karcinogene za ljude)
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 148/2023)
Czech Republic - Occupational Exposure Limits	
Local name	Beryllium
PEL (OEL TWA)	0.001 mg/m ³
NPK-P (OEL C)	0.002 mg/m ³
Remark	I - dráždí sliznice (oči, dýchací cesty) resp. kůže, K - karcinogen kategorie 1A a 1B (s větou H350, H350i), S - látka má senzibilizující účinek (s větou H317, H334), P - u látky nelze vyloučit závažné pozdní účinky (s větou H372, H373).
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 330/2023 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Beryllium, pulver og forbindelser
OEL TWA	0.001 mg/m ³ beregnet som Be
Remark	E (betyder, at stoffet har en EU-grænseværdi); K (betyder, at stoffet anses for at kunne være kræftfremkaldende og omfattet af bekendtgørelse om foranstaltninger til forebyggelse af risici ved arbejde med stoffer og materialer, der kan være kræftfremkaldende, mutagene eller reproduktionstoksiske). Hud- og luftvejssensibiliserende
Regulatory reference	BEK nr 1619 af 19/12/2024
Estonia - Occupational Exposure Limits	
Local name	Berüllium ja berülliumi anorgaanilised ühendid
OEL TWA	0.0002 mg/m ³ Sissehingatast fraktsioon (kehtib alates 11.07.2026) 0.0006 mg/m ³ (kehtib kuni 10.07.2026)
Remark	C (Kantserogeenne aine), S (Sensibiliseeriv aine), 6 (Metalliline berüllium ei ole sensibiliseeriv)
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 02.04.2024, 13)
Finland - Occupational Exposure Limits	
Local name	Beryllium, metalli
HTP (OEL TWA)	0.0001 mg/m ³
HTP (OEL STEL)	0.0004 mg/m ³
Remark	Iho
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

beryllium nitrate (13597-99-4)	
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Beryllium und seine anorganischen Verbindungen
AGW (OEL TWA)	0.00006 mg/m ³ (A) 0.00014 mg/m ³ (E)
Peak exposure limitation factor	1(I)
Remark	AGS - Ausschuss für Gefahrstoffe; X - Krebserzeugender Stoff der Kat. 1A oder 1B oder krebserzeugende Tätigkeit oder Verfahren nach § 2 Absatz 3 Nr. 4 der Gefahrstoffverordnung – es ist zusätzlich § 10 GefStoffV zu beachten; 10 - Der Arbeitsplatzgrenzwert bezieht sich auf den Elementgehalt des entsprechenden Metalls
Regulatory reference	TRGS900
Hungary - Occupational Exposure Limits	
Local name	BERILLIUM ÉS VEGYÜLETEI (Be-ra számítva)
AK (OEL TWA)	0.0006 mg/m ³
Remark	k(1B) (rákkeltő), b (Bőrön át is felszívódik); T (Azok az anyagok, amelyek egészségkárosító hatása TARTÓS expozíciót követően jelentkezik)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	Beryllium and beryllium compounds (as Be)
OEL TWA	0.0002 mg/m ³
Remark	BOELV (Binding Occupational Exposure Limit Values), Sens (In the workplace, respiratory or dermal exposures to sensitising agents may occur. Sensitisers may evoke respiratory or dermal reactions, e.g. asthma, rhinitis and allergic contact dermatitis. The "sens" notation alone does not distinguish between respiratory or dermal sensitisation. Chemical agents that are sensitisers present special problems in the workplace. Should an employee become sensitised, subsequent exposure may cause intense responses, even at low exposure concentrations well below the OELV. Exposure should be eliminated or significantly reduced through control measures such as engineering and process controls and use of personal protective equipment (PPE))
Regulatory reference	Chemical Agents Code of Practice 2024
Poland - Occupational Exposure Limits	
Local name	Beryl i jego związki nieorganiczne w przeliczeniu na Be
NDS (OEL TWA)	0.0002 mg/m ³
Remark	Substancja może mieć działanie uczulające na skórę i układ oddechowy. Frakcja wdychalna – frakcja aerozolu wnika przez nos i usta, która stwarza zagrożenie dla zdrowia po zdeponowaniu w drogach oddechowych.
Regulatory reference	Dz. U. 2024 poz. 1017 wraz z późn. zm.
Portugal - Occupational Exposure Limits	
Local name	Berílio e compostos, expressos em Be
OEL TWA	0.00005 mg/m ³ I (Fração inalável)
Remark	A1 (Agente carcinogénico confirmado no Homem). Compostos solúveis: P, SC. Compostos solúveis e insolúveis: SR
Regulatory reference	Norma Portuguesa NP 1796:2014

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

beryllium nitrate (13597-99-4)	
Romania - Occupational Exposure Limits	
Local name	Beriliu și compuși (exprimați în Be)
OEL TWA	0.002 mg/m ³
Slovenia - Occupational Exposure Limits	
Local name	berilij in anorganske berilijeve spojine
OEL TWA	0.0002 mg/m ³ 0.0006 mg/m ³
Remark	Rakotvorne snovi – kategorija 1B. EU, SK (Snov lahko povzroči preobčutljivost kože), SD (Snov lahko povzroči preobčutljivost dihalnih poti)
Regulatory reference	Uradni list RS, št. 29/2024 z dne 4.4.2024 - Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti rakotvornim ali mutagenim snovem
Spain - Occupational Exposure Limits	
Local name	Berilio
VLA-ED (OEL TWA)	0.0002 mg/m ³ elemental 0.0002 mg/m ³ Compuestos de berilio, como Be, excepto los expresamente indicados
Remark	Sen (Sensibilizante. Véase Apartado 6), r (Esta sustancia tiene establecidas restricciones a la fabricación, la comercialización o el uso en los términos especificados en el “Reglamento (CE) n° 1907/2006 sobre Registro, Evaluación, Autorización y Restricción de sustancias y preparados químicos” (REACH) de 18 de diciembre de 2006 (DOUE L 369 de 30 de diciembre de 2006). Las restricciones de una sustancia pueden aplicarse a todos los usos o sólo a usos concretos. El anexo XVII del Reglamento REACH contiene la lista de todas las sustancias restringidas y especifica los usos que se han restringido).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2024. INSHT
Sweden - Occupational Exposure Limits	
Local name	Beryllium, och föreningar (som Be)
NGV (OEL TWA)	0.002 mg/m ³ totaldamm
Remark	C (Ämnet är cancerframkallande. Risk för cancer finns även vid annan exponering än via inandning. För vissa cancerframkallande ämnen som inte har gränsvärden gäller förbud eller tillståndskrav enligt föreskrifterna om kemiska arbetsmiljörisker); S (Ämnet är sensibiliserande. Sensibiliserande ämnen kan ge allergi eller annan överkänslighet. Överkänslighetsbesvären drabbar främst huden eller andningsorganen. Överkänslighet innebär att man reagerar vid kontakt med ämnen som normalt inte ger besvär. Allergi är en undergrupp av överkänslighet som orsakas av reaktioner i kroppens immunsystem. Särskilt låga gränsvärden har fastställts för ämnen med mer uttalat luftvägssensibiliserande egenskaper. Några ämnen med starkt sensibiliserande egenskaper får endast hanteras efter tillstånd från Arbetsmiljöverket, se föreskrifterna om kemiska arbetsmiljörisker. Dessa ämnen har inga gränsvärden men i vissa fall riktvärden); 3 (Med totaldamm menas de partiklar (aerosoler) som fastnar på ett filter i den provtagare som beskrivs i Metodserien, Provtagning av totaldamm och respirabelt damm, Metod nr 1010, Arbetarskyddsstyrelsen, numera Arbetsmiljöverket. Filterdiametern är normalt 37 mm, men kan även vara 25 mm. Trots sitt namn provtas inte den totala mängden luftburna partiklar med denna metod)
Regulatory reference	Hygieniska gränsvärden (AFS 2020:6)
United Kingdom - Occupational Exposure Limits	
Local name	Beryllium
WEL TWA (OEL TWA)	0.002 mg/m ³ Beryllium compounds (as Be); United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

beryllium nitrate (13597-99-4)	
Remark	Carc (Capable of causing cancer and/or heritable genetic damage. See paragraphs 49–51)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Iceland - Occupational Exposure Limits	
Local name	Beryllíum og ólífræn beryllíum efna-sambönd, reiknað sem beryllíum (Be)
OEL TWA	0.0006 mg/m ³ örfínt ryk (gildir til 11. júlí 2026) 0.0002 mg/m ³ örfínt ryk
Remark	H (efnið getur auðveldlega borist inn í líkamann gegnum húð), K (efnið er krabbameinsvaldandi). Ertir öndunarfæri
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 1137/2020)
North Macedonia - Occupational Exposure Limits	
Local name	Берилиум и неговите соединенија освен алуминиум берилиум силикат и оние што се утврдени други места во овој анекс
OEL TWA	0.005 mg/m ³ мелење; (I) инхалабилна фракција – дел на вкупно суспендирани материји, кои работникот ги вдишува 0.002 mg/m ³ друго; (I) инхалабилна фракција – дел на вкупно суспендирани материји, кои работникот ги вдишува
KTV	4
Short time value [mg/m ³]	0.02 mg/m ³
Remark	(KTV) краткотрајна вредност (КТВ) значи концентрација на опасни хемиски супстанции во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покусо време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m ³ или во ml/m ³ (ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност; (ТДК) техничко достигнување на концентрацијата – е дадено за канцерогените супстанции и значи концентрација на супстанции во воздухот на работното место, кои можат да се достигнат со достапните техники
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)
USA - ACGIH - Occupational Exposure Limits	
Local name	Beryllium and compounds, as Be
ACGIH OEL TWA	0.00005 mg/m ³
Remark (ACGIH)	Beryllium sens; chronic beryllium; Skin; DSEN; RSEN; A1 (Confirmed Human Carcinogen: The agent is carcinogenic to humans based on the weight of evidence from epidemiologic studies)
Regulatory reference	ACGIH 2024
nitric acid (7697-37-2)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Nitric acid
IOEL STEL	2.6 mg/m ³

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

nitric acid (7697-37-2)	
	1 ppm
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
Albania - Occupational Exposure Limits	
Local name	Acid nitrik
OEL STEL	2.6 mg/m ³
	1 ppm
Regulatory reference	VENDIM Nr. 522, datë 6.8.2014 PËR MIRATIMIN E RREGULLORES "PËR MBROJTJEN E SIGURISË DHE SHËNDETIT TË PUNËMARRËSVE NGA RISQET E LIDHURA ME AGJENTËT KIMIKË NË PUNË"
Austria - Occupational Exposure Limits	
Local name	Salpetersäure
OEL C	2.6 mg/m ³
	1 ppm
Regulatory reference	BGBl. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	Acide nitrique # Salpeterzuur
OEL STEL	2.6 mg/m ³
	1 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
Bulgaria - Occupational Exposure Limits	
Local name	Азотна киселина
OEL STEL	2.6 mg/m ³
	1 ppm
Remark	• (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 28 от 2024 г., в сила от 05.04.2024 г.)
Croatia - Occupational Exposure Limits	
Local name	Dušična kiselina
KGVI (OEL STEL)	2.6 mg/m ³
	1 ppm
Remark	Direktiva: 2006/15/EZ
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, граничним vrijednostima izloženosti i biološkim граничним vrijednostima (NN 148/2023)
Cyprus - Occupational Exposure Limits	
Local name	Νιτρικό οξύ
OEL STEL	2.6 mg/m ³
	1 ppm
Regulatory reference	Κανονισμοί του 2007 (Κ.Δ.Π. 295/2007)

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

nitric acid (7697-37-2)	
Czech Republic - Occupational Exposure Limits	
Local name	Kyselina dusičná
PEL (OEL TWA)	1 mg/m ³
	0.38 ppm
NPK-P (OEL C)	2.5 mg/m ³
	0.95 ppm
Remark	I - dráždí sliznice (oči, dýchací cesty) resp. kůži.
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 330/2023 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Salpetersyre
OEL STEL	2.6 mg/m ³
	1 ppm
Remark	E (betyder, at stoffet har en EU-grænseværdi)
Regulatory reference	BEK nr 1619 af 19/12/2024
Estonia - Occupational Exposure Limits	
Local name	Lämmastikhape
OEL STEL	2.6 mg/m ³
	1 ppm
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 02.04.2024, 13)
Finland - Occupational Exposure Limits	
Local name	Typpihappo
HTP (OEL TWA)	1.3 mg/m ³
	0.5 ppm
HTP (OEL STEL)	2.6 mg/m ³
	1 ppm
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
France - Occupational Exposure Limits	
Local name	Acide nitrique
VLE (OEL C/STEL)	2.6 mg/m ³
	1 ppm
Remark	Valeurs réglementaires indicatives
Regulatory reference	Arrêté du 30 juin 2004 modifié (réf.: INRS ED 6443, 2022; Outil65; Arrêté du 26 octobre 2007)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Salpetersäure
AGW (OEL TWA)	2.6 mg/m ³
	1 ppm

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

nitric acid (7697-37-2)	
Remark	EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); 13 - Eine Begründung für die Ableitung eines gesundheitsbasierten AGW liegt nicht vor; 16 - Der Arbeitsplatzgrenzwert ist nur als Kurzzeitwert festgelegt. Die betriebliche Überwachung soll durch messtechnische Mittelwertbildung über 15 Minuten erfolgen, z.B. durch eine 15-minütige Probenahme
Regulatory reference	TRGS900
Gibraltar - Occupational Exposure Limits	
Local name	Nitric acid
OEL STEL	2.6 mg/m ³ 1 ppm
Regulatory reference	Factories (Control of Chemical Agents at Work) Regulations 2003 (LN. 2018/181)
Greece - Occupational Exposure Limits	
Local name	Νιτρικό οξύ
OEL STEL	2.6 mg/m ³ 1 ppm
Regulatory reference	Π.Δ. 162/2007 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
Local name	SALÉTROMSAV
CK (OEL STEL)	2.6 mg/m ³ 1 ppm
Remark	i (ingerlő anyag, amely izgatja a bőrt, nyálkahártyát, szemet vagy mindhármát), m (maró hatású anyag, amely felmarja a bőrt, nyálkahártyát, szemet vagy mindhármát); EU2 (2006/15/EK irányelvben közölt érték)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	Nitric acid
OEL STEL	2.6 mg/m ³ 1 ppm
Remark	IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2024
Italy - Occupational Exposure Limits	
Local name	Acido nitrico
OEL STEL	2.6 mg/m ³ 1 ppm
Regulatory reference	Allegato XXXVIII del Decreto Legislativo 4 settembre 2024, n. 135
Latvia - Occupational Exposure Limits	
Local name	Slāpekšķābe
OEL TWA	2 mg/m ³ 0.78 ppm

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

nitric acid (7697-37-2)	
OEL STEL	2.6 mg/m ³
	1 ppm
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325 (Grozījumi Ministru kabineta 2024. gada 26. martā noteikumiem Nr. 191).
Lithuania - Occupational Exposure Limits	
Local name	Nitrato rūgštis (azoto rūgštis)
TPRV (OEL STEL)	2.6 mg/m ³
	1 ppm
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Luxembourg - Occupational Exposure Limits	
Local name	Acide nitrique
OEL STEL	2.6 mg/m ³
	1 ppm
Regulatory reference	Mémorial A N° 226 de 2021 concernant la protection de la sécurité et de la santé des salariés contre les risques liés à des agents chimiques sur le lieu de travail
Malta - Occupational Exposure Limits	
Local name	Nitric acid
OEL STEL	2.6 mg/m ³
	1 ppm
Regulatory reference	S.L. 424.24 - Chemical Agents at Work Regulations (L.N. 356 of 2021) # L.S. 424.24 - Regolamenti dwar Aġenti Kimiċi fuq il-Post tax-Xogħol (A.L. 356 tal-2021)
Netherlands - Occupational Exposure Limits	
Local name	Salpeterzuur
TGG-15min (OEL STEL)	1.3 mg/m ³
	0.5 ppm (Salpeterzuur; Netherlands; Short time value; Public occupational exposure limit value)
Regulatory reference	Arbeidsomstandighedenregeling 2024
Portugal - Occupational Exposure Limits	
Local name	Ácido nítrico
OEL TWA	2 ppm
OEL STEL	4 ppm
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Acid nitric/Acid azotic
OEL STEL	2.6 mg/m ³
	1 ppm
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 179/2024)
Serbia - Occupational Exposure Limits	
Local name	азотна киселина

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

nitric acid (7697-37-2)	
OEL STEL	3 mg/m ³
	1 ppm
Remark	ЕУ** – напомена да се ради о хемијским материјама за које су утврђене индикативне граничне вредности изложености према Директиви 2006/15/ЕЗ (друга листа)
Regulatory reference	ПРАВИЛНИК о превентивним мерама за безбедан и здрав рад при излагању хемијским материјама („Службени гласник РС”, бр. 106/09, 117/17 и 107/21)
Slovakia - Occupational Exposure Limits	
Local name	Kyselina dusičná
NPHV (OEL STEL)	2.6 mg/m ³
	1 ppm
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (122/2024 Z. z.)
Slovenia - Occupational Exposure Limits	
Local name	dušikova kislina
OEL TWA	2.6 mg/m ³
	1 ppm
OEL STEL	2.6 mg/m ³
	1 ppm
Remark	EU
Regulatory reference	Uradni list RS, št. 29/2024 z dne 4. 4. 2024 - Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu
Spain - Occupational Exposure Limits	
Local name	Ácido nítrico
VLA-EC (OEL STEL)	2.6 mg/m ³
	1 ppm
Remark	VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2024. INSHT
Sweden - Occupational Exposure Limits	
Local name	Salpetersyra
NGV (OEL TWA)	1.3 mg/m ³
	0.5 ppm
KGV (OEL STEL)	2.6 mg/m ³
	1 ppm
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	Nitric acid
WEL STEL (OEL STEL)	2.6 mg/m ³
	1 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

nitric acid (7697-37-2)	
Iceland - Occupational Exposure Limits	
Local name	Saltpéturssýra
OEL STEL	2.6 mg/m ³
	1 ppm
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
Norway - Occupational Exposure Limits	
Local name	Salpetersyre
Grenseverdi (OEL TWA)	5 mg/m ³
	2 ppm
Remark	E: EU har en veiledende grenseverdi og/eller anmerkning for stoffet.
Regulatory reference	FOR-2024-04-05-581
North Macedonia - Occupational Exposure Limits	
Local name	азотна киселина
OEL TWA	2.6 mg/m ³
	1 ppm
KTV	1
Short time value [mg/m ³]	2.6 mg/m ³
Short time value [ppm]	1 ppm
Remark	(KTV) краткотрајна вредност (КТВ) значи концентрација на опасни хемиски супстанции во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покусо време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m ³ или во ml/m ³ (ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност; (EU) European Union – гранична вредност, определена на ниво на Европската унија; (*) дополнување на граничната вредност заради донесената Директива на Комисијата 2006/15ES од 7 февруари 2006 за создавање на втора листа на индикативни гранични вредности за професионална изложеност според директивата 98/24/ЕС и за измените на директивата 91/322/ЕЕС и директивата 2000/39/ ЕС (Сл. весник бр. 38 од ден 9.2.2006, стр. 36)
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)
Switzerland - Occupational Exposure Limits	
Local name	Acide nitrique / Salpetersäure
MAK (OEL TWA)	5 mg/m ³
	2 ppm
KZGW (OEL STEL)	5 mg/m ³
	2 ppm
Remark	NIOSH, OSHA

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

nitric acid (7697-37-2)	
Regulatory reference	www.suva.ch, 01.01.2025
USA - ACGIH - Occupational Exposure Limits	
Local name	Nitric acid
ACGIH OEL TWA	2 ppm
ACGIH OEL STEL	4 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr; dental erosion
Regulatory reference	ACGIH 2024
hydrofluoric Acid (7664-39-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Hydrogen fluoride
IOEL TWA	1.5 mg/m ³
	1.8 ppm
IOEL STEL	2.5 mg/m ³
	3 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
EU - Biological Limit Value (BLV)	
Local name	Hydrogen fluoride
BLV	8 mg/l Parameter: F - Medium: urine - Sampling time: end of shift
Regulatory reference	SCOEL List of recommended health-based BLVs and BGVs
Albania - Occupational Exposure Limits	
Local name	Fluorur hidrogjeni
OEL TWA	1.5 mg/m ³
	1.8 ppm
OEL STEL	2.5 mg/m ³
	3 ppm
Regulatory reference	VENDIM Nr. 522, datë 6.8.2014 PËR MIRATIMIN E RREGULLORES "PËR MBROJTJEN E SIGURISË DHE SHËNDËTIT TË PUNËMARRËSVE NGA RISQET E LIDHURA ME AGJENTËT KIMIKË NË PUNË"
Austria - Occupational Exposure Limits	
Local name	Fluorwasserstoff (Flusssäure; Hydrogenfluorid)
MAK (OEL TWA)	1.5 mg/m ³
	1.8 ppm
MAK (OEL STEL)	2.5 mg/m ³ (4x 15(Miw) min)
	3 ppm (4x 15(Miw) min)
Remark	H
Regulatory reference	BGBl. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	Hydrogène (fluorure d') # Waterstofffluoride

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

hydrofluoric Acid (7664-39-3)	
OEL TWA	1.5 mg/m ³
	1.8 ppm
OEL STEL	2.5 mg/m ³
	3 ppm
Remark	M: la mention "M" indique que lors d'une exposition supérieure à la valeur limite, des irritations apparaissent ou un danger d'intoxication aiguë existe. Le procédé de travail doit être conçu de telle façon que l'exposition ne dépasse jamais la valeur limite. Lors des mesurages, la période d'échantillonnage doit être aussi courte que possible afin de pouvoir effectuer des mesurages fiables. Le résultat des mesurages est calculé en fonction de la période d'échantillonnage. # M: de vermelding "M" duidt aan dat bij de blootstelling boven de grenswaarde irritatie optreedt of er gevaar bestaat voor acute vergiftiging. Het werkproces moet zo zijn ontworpen dat de blootstelling de grenswaarde nooit overschrijdt. Bij een controle geldt dat de bemonsterde periode zo kort mogelijk moet zijn om een betrouwbare meting te kunnen verrichten. Het meetresultaat wordt dan gerelateerd aan de beschouwde periode.
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
Bulgaria - Occupational Exposure Limits	
Local name	Флуороводород
OEL TWA	1.5 mg/m ³
	1.8 ppm
OEL STEL	2.5 mg/m ³
	3 ppm
Remark	• (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 28 от 2024 г., в сила от 05.04.2024 г.)
Croatia - Occupational Exposure Limits	
Local name	Vodikov fluorid
GVI (OEL TWA)	1.5 mg/m ³
	1.8 ppm
KGVI (OEL STEL)	2.5 mg/m ³
	3 ppm
Remark	Direktiva: 2000/39/EZ
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 148/2023)
Croatia - Biological limit values	
Local name	Fluorovodična kiselina (vodikov fluorid) i anorganski fluorovi spojevi

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

hydrofluoric Acid (7664-39-3)	
BLV	8 mg/g creatinine Karakteristični pokazatelj: fluoridi - Biološki uzorak: mokraća - Vrijeme uzorkovanja: na kraju radne smjene 40 mmol/mol Creatinine Karakteristični pokazatelj: fluoridi - Biološki uzorak: mokraća - Vrijeme uzorkovanja: na kraju radne smjene 4 mg/g creatinine Karakteristični pokazatelj: fluoridi - Biološki uzorak: mokraća - Vrijeme uzorkovanja: prije početka radne smjene u sredini tjedna 24 mmol/mol Creatinine Karakteristični pokazatelj: fluoridi - Biološki uzorak: mokraća - Vrijeme uzorkovanja: prije početka radne smjene u sredini tjedna
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 91/2018)
Cyprus - Occupational Exposure Limits	
Local name	Υδροφθόριο
OEL TWA	1.5 mg/m ³
	1.8 ppm
OEL STEL	2.5 mg/m ³
	3 ppm
Regulatory reference	Κανονισμοί του 2007 (Κ.Δ.Π. 295/2007)
Czech Republic - Occupational Exposure Limits	
Local name	Fluorovodík
PEL (OEL TWA)	1.5 mg/m ³
	1.8 ppm
NPK-P (OEL C)	2.5 mg/m ³
	3 ppm
Remark	I - dráždí sliznice (oči, dýchací cesty) resp. kůži.
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 330/2023 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Hydrogenfluorid (Fluorbrinte)
OEL TWA	1.5 mg/m ³
	1.8 ppm
OEL STEL	2.5 mg/m ³
	3 ppm
Remark	E (betyder, at stoffet har en EU-grænseværdi)
Regulatory reference	BEK nr 1619 af 19/12/2024
Estonia - Occupational Exposure Limits	
Local name	Vesinikfluoriid
OEL TWA	1.5 mg/m ³
	1.8 ppm
OEL STEL	2.5 mg/m ³
	3 ppm
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 02.04.2024, 13)

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

hydrofluoric Acid (7664-39-3)	
Finland - Occupational Exposure Limits	
Local name	Fluorivety
HTP (OEL TWA)	1.5 mg/m ³
	1.8 ppm
HTP (OEL STEL)	2.5 mg/m ³
	3 ppm
Remark	lho
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveystieteiden ministeriö)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Fluorwasserstoff
AGW (OEL TWA)	0.83 mg/m ³
	1 ppm
Peak exposure limitation factor	2(l)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden; H - hautresorptiv
Regulatory reference	TRGS900
Germany - Biological limit values (TRGS 903)	
Local name	Hydrogenfluorid (Fluorwasserstoff) und anorganische Fluorverbindungen (Fluoride)
Biological limit value	4 mg/l Parameter: Fluorid - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende - Festlegung/Begründung: 11/2020 DFG
Regulatory reference	TRGS 903
Gibraltar - Occupational Exposure Limits	
Local name	Hydrogen fluoride
OEL TWA	1.5 mg/m ³
	1.8 ppm
OEL STEL	2.5 mg/m ³
	3 ppm
Regulatory reference	Factories (Control of Chemical Agents at Work) Regulations 2003 (LN. 2018/181)
Greece - Occupational Exposure Limits	
Local name	Υδροφθόριο
OEL TWA	2.5 mg/m ³
	3 ppm
OEL STEL	2.5 mg/m ³
	3 ppm
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

hydrofluoric Acid (7664-39-3)	
Hungary - Occupational Exposure Limits	
Local name	HIDROGÉN-FLUORID
AK (OEL TWA)	1.5 mg/m ³
CK (OEL STEL)	2.5 mg/m ³
Remark	b (Bőrön át is felszívódik), m (maró hatású anyag, amely felmarja a bőrt, nyálkahártyát, szemet vagy mindhármat), BEM (biológiai expozíciós mutató); EU1 (2000/39/EK irányelvben közölt érték); N (Irritáló anyagok, egyszerű fojtógázok, csekély egészségkárosító hatással bíró anyagok)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	Hydrogen fluoride (as F)
OEL TWA	1.5 mg/m ³ 1.8 ppm
OEL STEL	2.5 mg/m ³ 3 ppm
Remark	IOELV (Indicative Occupational Exposure Limit Values), Skin (Substances which have the capacity to penetrate intact skin when they come in contact with it and be absorbed into the body. A substantial contribution to the total body burden via dermal exposure is possible)
Regulatory reference	Chemical Agents Code of Practice 2024
Italy - Occupational Exposure Limits	
Local name	Acido fluoridrico
OEL TWA	1.5 mg/m ³ 1.8 ppm
OEL STEL	2.5 mg/m ³ 3 ppm
Regulatory reference	Allegato XXXVIII del Decreto Legislativo 4 settembre 2024, n. 135
Latvia - Occupational Exposure Limits	
Local name	Fluorūdeņradis
OEL TWA	1.5 mg/m ³ 1.8 ppm
OEL STEL	2.5 mg/m ³ 3 ppm
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325 (Grozījumi Ministru kabineta 2024. gada 26. martā noteikumiem Nr. 191).
Lithuania - Occupational Exposure Limits	
Local name	Vandenilio fluoridas
IPRV (OEL TWA)	1.5 mg/m ³ 1.8 ppm
TPRV (OEL STEL)	2.5 mg/m ³

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

hydrofluoric Acid (7664-39-3)	
	3 ppm
Remark	Ū (ūmus poveikis)
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Luxembourg - Occupational Exposure Limits	
Local name	Fluorure d'hydrogène
OEL TWA	1.5 mg/m ³
	1.8 ppm
OEL STEL	2.5 mg/m ³
	3 ppm
Regulatory reference	Mémorial A N° 226 de 2021 concernant la protection de la sécurité et de la santé des salariés contre les risques liés à des agents chimiques sur le lieu de travail
Malta - Occupational Exposure Limits	
Local name	Hydrogen fluoride
OEL TWA	1.5 mg/m ³
	1.8 ppm
OEL STEL	2.5 mg/m ³
	3 ppm
Regulatory reference	S.L. 424.24 - Chemical Agents at Work Regulations (L.N. 356 of 2021) # L.S. 424.24 - Regolamenti dwar Aġenti Kimiċi fuq il-Post tax-Xogħol (A.L. 356 tal-2021)
Netherlands - Occupational Exposure Limits	
Local name	Fluorwaterstof
TGG-15min (OEL STEL)	1 mg/m ³ (als F)
	1.2 ppm (Fluorwaterstof (als F); Netherlands; Short time value; Public occupational exposure limit value; als F)
Regulatory reference	Arbeidsomstandighedenregeling 2024
Poland - Occupational Exposure Limits	
Local name	Fluorowodór
NDS (OEL TWA)	0.5 mg/m ³
NDSch (OEL STEL)	2 mg/m ³
Regulatory reference	Dz. U. 2024 poz. 1017 wraz z późn. zm.
Portugal - Occupational Exposure Limits	
Local name	Ácido fluorídrico, expresso em F
OEL TWA	0.5 ppm
OEL C	2 mg/m ³
	2 ppm
Remark	P (Toxicidade percutânea); IBE (Índice biológico de exposição)
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Acid fluorhidric/Fluorură de hidrogen

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

hydrofluoric Acid (7664-39-3)	
OEL TWA	1.5 mg/m ³
	1.8 ppm
OEL STEL	2.5 mg/m ³
	3 ppm
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 179/2024)
Serbia - Occupational Exposure Limits	
Local name	водоник флуорид, флуороводоник
OEL TWA	2 mg/m ³
	2 ppm
OEL STEL	3 mg/m ³
	3 ppm
Remark	ЕУ* – напомена да се ради о хемијским материјама за које су утврђене индикативне граничне вредности изложености према Директиви 2000/39/ЕЗ (прва листа)
Regulatory reference	ПРАВИЛНИК о превентивним мерама за безбедан и здрав рад при излагању хемијским материјама („Службени гласник РС”, бр. 106/09, 117/17 и 107/21)
Slovakia - Occupational Exposure Limits	
Local name	Fluórovodík, kyselina fluorovodíková (ako F)
NPHV (OEL TWA)	1.5 mg/m ³
	1.8 ppm
NPHV (OEL STEL)	2.5 mg/m ³
	3 ppm
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (122/2024 Z. z.)
Slovakia - Biological limit values	
Local name	Fluorovodík a anorganické zlúčeniny fluóru (fluoridy)
BLV	7 mg/g creatinine Zisťovaný faktor: Fluoridy - Vyšetovaný materiál: moč - Čas odberu vzorky: b) koniec expozície alebo pracovnej zmeny 4 mg/g creatinine Zisťovaný faktor: Fluoridy - Vyšetovaný materiál: moč - Čas odberu vzorky: d) pred nasledujúcou pracovnou zmenou
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (122/2024 Z. z.)
Slovenia - Occupational Exposure Limits	
Local name	vodikov fluorid
OEL TWA	1.5 mg/m ³
	1.8 ppm
OEL STEL	2.25 mg/m ³
	2.7 ppm
Remark	K (Lastnost lažjega prehajanja snovi v organizem skozi kožo), Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti), BAT (Biološka mejna vrednost), EU
Regulatory reference	Uradni list RS, št. 29/2024 z dne 4. 4. 2024 - Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

hydrofluoric Acid (7664-39-3)	
Slovenia - Biological limit values	
Local name	vodikov fluorid in anorganske fluorove spojine (fluoridi)
BLV	7 mg/g creatinine Parameter: fluorid - Biološki vzorec: urin - Čas vzorčenja: ob koncu delovne izmene 4 mg/g creatinine Parameter: fluorid - Biološki vzorec: urin - Čas vzorčenja: pred naslednjim delovnim dnevom
Regulatory reference	Uradni list RS, št. 29/24 z dne 4. 4. 2024 - Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu
Spain - Occupational Exposure Limits	
Local name	Fluoruro de hidrógeno
VLA-ED (OEL TWA)	1.5 mg/m ³ 1.8 ppm
VLA-EC (OEL STEL)	2.5 mg/m ³ 3 ppm
Remark	VLB® (Agente químico que tiene Valor Límite Biológico), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2024. INSHT
Spain - Biological limit values	
Local name	Fluoruro de hidrógeno
BLV	2 mg/l Parámetro: Fluoruros - Medio: Orina - Momento de muestreo: Antes de la jornada laboral - Notas: F (Fondo. El indicador está generalmente presente en cantidades detectables en personas no expuestas laboralmente. Estos niveles de fondo están considerados en el valor VLB), I (Significa que el indicador biológico es inespecífico puesto que puede encontrarse después de la exposición a otros agentes químicos) 3 mg/l Parámetro: Fluoruros - Medio: Orina - Momento de muestreo: Final de la jornada laboral - Notas: F (Fondo. El indicador está generalmente presente en cantidades detectables en personas no expuestas laboralmente. Estos niveles de fondo están considerados en el valor VLB), I (Significa que el indicador biológico es inespecífico puesto que puede encontrarse después de la exposición a otros agentes químicos)
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2024. INSHT
Sweden - Occupational Exposure Limits	
Local name	Vätefluorid (Fluorväte)
NGV (OEL TWA)	1.5 mg/m ³ 1.8 ppm
KGV (OEL STEL)	1.7 mg/m ³ 2 ppm
Remark	31 (Vid exponering för blandningar av fluorider och vätefluorid ska nivågränsvärdet för fluorider tillämpas)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	Hydrogen fluoride
WEL TWA (OEL TWA)	1.5 mg/m ³ (as F) 1.8 ppm (as F)

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

hydrofluoric Acid (7664-39-3)	
WEL STEL (OEL STEL)	2.5 mg/m ³ (as F) 3 ppm (as F)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Iceland - Occupational Exposure Limits	
Local name	Vetnisflúoríð (flúorvetni)
OEL TWA	0.6 mg/m ³ 0.7 ppm
OEL STEL	2.5 mg/m ³ Þakgildið er miðað við fimm mínútna tímabil 3 ppm Þakgildið er miðað við fimm mínútna tímabil
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
Norway - Occupational Exposure Limits	
Local name	Hydrogenfluorid (Fluss-syre)
Grenseverdi (OEL TWA)	0.5 mg/m ³ 0.6 ppm
Korttidsverdi (OEL STEL)	1.5 mg/m ³ 1.8 ppm
Remark	H: Kjemikalier som kan tas opp gjennom huden; E: EU har en veiledende grenseverdi og/eller anmerkning for stoffet.
Regulatory reference	FOR-2024-04-05-581
North Macedonia - Occupational Exposure Limits	
Local name	Флуороводород
OEL TWA	1.5 mg/m ³ 1.8 ppm
KTV	1.5
Short time value [mg/m ³]	2.25 mg/m ³
Short time value [ppm]	2.7 ppm
Remark	(KTV) краткотрајна вредност (КТВ) значи концентрација на опасни хемиски супстанции во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покусо време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m ³ или во ml/m ³ (ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност; (BAT) биолошка гранична вредност – праг на биолошка гранична вредност, што значи предупредување на опасна хемиска супстанца и нејзини метаболити во ткивата, телесните течности или издишувањето на воздухот, без оглед на тоа, дали опасната хемиска супстанца е внесена во организмот со вдишување, голтање или преку кожата; (EU) European Union – гранична вредност, определена на ниво на Европската унија
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

hydrofluoric Acid (7664-39-3)	
Switzerland - Occupational Exposure Limits	
Local name	Acide fluorhydrique / Fluorwasserstoff
MAK (OEL TWA)	0.83 mg/m ³
	1 ppm
KZGW (OEL STEL)	1.66 mg/m ³
	2 ppm
Notation	SS _C , B / SS _C , B
Remark	HSE, NIOSH, OSHA
Regulatory reference	www.suva.ch, 01.01.2025
Switzerland - BAT	
Local name	Fluorures / Fluorwasserstoff
BAT	4 mg/l (211 µmol/l; Paramètre biologique: Fluorures; Substrat d'examen: Urine; Moment du prélèvement: Fin de l'exposition, de la période de travail.) / (211 µmol/l; Biologischer Parameter: Fluorid; Untersuchungsmaterial: Urin; Probenahmezeitpunkt: Expositionsende, bzw. Schichtende.)
Remark	Influence de l'environnement. / Umwelteinflüsse.
Regulatory reference	Ordonnance 832.30 (OPA), article 50 al. 3, www.suva.ch/valeurs-limites / Verordnung 832.30 (VUV), Art. 50 Abs. 3, www.suva.ch/grenzwerte
USA - ACGIH - Occupational Exposure Limits	
Local name	Hydrogen fluoride, as F
ACGIH OEL TWA	0.5 ppm
ACGIH OEL C	2 ppm
Remark (ACGIH)	TLV® Basis: URT, LRT, skin, & eye irr; fluorosis. Notations: Skin; BEI
Regulatory reference	ACGIH 2024

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure. Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the protective equipment.

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Safety glasses

Skin protection

Skin and body protection:

Wear suitable protective clothing

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hand protection:

Protective gloves

Respiratory protection

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Not available
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: ≈ 0 °C
Boiling point	: ≈ 100 °C
Flammability	: Non flammable.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: < 2
Viscosity, kinematic	: Not available
Solubility	: Miscible with water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 1.01
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Toxic in contact with skin.
Acute toxicity (inhalation) : Not classified

ICP Standard Solution Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

ATE CLP (oral)	871.384 mg/kg bodyweight
ATE CLP (dermal)	1000 mg/kg bodyweight

nitric acid (7697-37-2)

LC50 Inhalation - Rat	> 2.65 mg/L air
-----------------------	-----------------

hydrofluoric Acid (7664-39-3)

LD50 dermal rabbit	≤ 50 mg/kg
--------------------	------------

Skin corrosion/irritation : Causes skin irritation.
pH: < 2

hydrofluoric Acid (7664-39-3)

pH	< 1
----	-----

Serious eye damage/irritation : Causes serious eye irritation.
pH: < 2

hydrofluoric Acid (7664-39-3)

pH	< 1
----	-----

Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : May cause cancer.

beryllium nitrate (13597-99-4)

IARC group	1 - Carcinogenic to humans
------------	----------------------------

Reproductive toxicity : Not classified
STOT-single exposure : Not classified

beryllium nitrate (13597-99-4)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

beryllium nitrate (13597-99-4)

STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
------------------------	---

nitric acid (7697-37-2)

NOAEL (oral, rat, 90 days)	1500 mg/kg bodyweight
NOAEC (inhalation, rat, gas, 90 days)	2.15 ppm

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Aspiration hazard : Not classified

nitric acid (7697-37-2)

Viscosity, kinematic	0.595 mm ² /s
----------------------	--------------------------

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

beryllium nitrate (13597-99-4)

LC50 - Fish [1]	8 mg/l
-----------------	--------

EC50 - Crustacea [1]	18 mg/l (24h)
----------------------	---------------

nitric acid (7697-37-2)

EC50 - Crustacea [1]	180 mg/l Daphnia magna (Water flea)
----------------------	-------------------------------------

Threshold limit - Algae [1]	> 19 mg/l
-----------------------------	-----------

hydrofluoric Acid (7664-39-3)

EC50 - Crustacea [1]	270 mg/l Daphnia magna (Water flea)
----------------------	-------------------------------------

NOEC (chronic)	14.1 mg/l Daphnia magna (Water flea)
----------------	--------------------------------------

NOEC chronic fish	4 mg/l Oncorhynchus mykiss (Rainbow trout)
-------------------	--

12.2. Persistence and degradability

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

beryllium nitrate (13597-99-4)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

nitric acid (7697-37-2)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

hydrofluoric Acid (7664-39-3)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

12.3. Bioaccumulative potential

beryllium nitrate (13597-99-4)

Bioaccumulative potential	Not bioaccumulative.
---------------------------	----------------------

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

nitric acid (7697-37-2)

Partition coefficient n-octanol/water (Log Pow) -2.3

hydrofluoric Acid (7664-39-3)

Partition coefficient n-octanol/water (Log Pow) -1.4

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Component

Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII beryllium nitrate (13597-99-4), nitric acid (7697-37-2), hydrofluoric Acid (7664-39-3)

Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII beryllium nitrate (13597-99-4), nitric acid (7697-37-2), hydrofluoric Acid (7664-39-3)

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Disposal must be done according to official regulations.
Additional information : Do not re-use empty containers.
Ecological waste information : Avoid release to the environment.
European List of Waste (LoW, EC 2000/532) : 16 05 06* - laboratory chemicals consisting of or containing dangerous substances including mixtures of laboratory chemicals

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID






ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 3287	UN 3287	UN 3287	UN 3287	UN 3287
14.2. UN proper shipping name				
TOXIC LIQUID, INORGANIC, N.O.S. (beryllium nitrate ; hydrofluoric Acid)	TOXIC LIQUID, INORGANIC, N.O.S. (beryllium nitrate ; hydrofluoric Acid)	Toxic liquid, inorganic, n.o.s. (beryllium nitrate ; hydrofluoric Acid)	TOXIC LIQUID, INORGANIC, N.O.S. (beryllium nitrate ; hydrofluoric Acid)	TOXIC LIQUID, INORGANIC, N.O.S. (beryllium nitrate ; hydrofluoric Acid)

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
Transport document description				
UN 3287 TOXIC LIQUID, INORGANIC, N.O.S. (beryllium nitrate ; hydrofluoric Acid), 6.1, III, (E)	UN 3287 TOXIC LIQUID, INORGANIC, N.O.S. (beryllium nitrate ; hydrofluoric Acid), 6.1, III	UN 3287 Toxic liquid, inorganic, n.o.s. (beryllium nitrate ; hydrofluoric Acid), 6.1, III	UN 3287 TOXIC LIQUID, INORGANIC, N.O.S. (beryllium nitrate ; hydrofluoric Acid), 6.1, III	UN 3287 TOXIC LIQUID, INORGANIC, N.O.S. (beryllium nitrate ; hydrofluoric Acid), 6.1, III
14.3. Transport hazard class(es)				
6.1	6.1	6.1	6.1	6.1
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-A EmS-No. (Spillage): S-A	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: T4
Special provisions (ADR)	: 274
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T7
Portable tank and bulk container special provisions (ADR)	: TP1, TP28
Tank code (ADR)	: L4BH
Tank special provisions (ADR)	: TU15, TE19
Vehicle for tank carriage	: AT
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13, CV28
Special provisions for carriage - Operation (ADR)	: S9
Hazard identification number (Kemler No.)	: 60
Orange plates	:



Tunnel restriction code (ADR)	: E
EAC code	: 2X
APP code	: B

Transport by sea

Special provisions (IMDG)	: 223, 274
---------------------------	------------

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP1, TP28
Stowage category (IMDG)	: A
Stowage and handling (IMDG)	: SW2
Properties and observations (IMDG)	: Toxic if swallowed, by skin contact or by inhalation.

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y642
PCA limited quantity max net quantity (IATA)	: 2L
PCA packing instructions (IATA)	: 655
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 663
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3, A4, A137
ERG code (IATA)	: 6L

Inland waterway transport

Classification code (ADN)	: T4
Special provisions (ADN)	: 274, 802
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EP, TOX, A
Ventilation (ADN)	: VE02
Number of blue cones/lights (ADN)	: 0

Rail transport

Classification code (RID)	: T4
Special provisions (RID)	: 274
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T7
Portable tank and bulk container special provisions (RID)	: TP1, TP28
Tank codes for RID tanks (RID)	: L4BH
Special provisions for RID tanks (RID)	: TU15
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W12
Special provisions for carriage - Loading, unloading and handling (RID)	: CW13, CW28, CW31
Colis express (express parcels) (RID)	: CE8
Hazard identification number (RID)	: 60

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

ICP Standard Solution Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	nitric acid	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	ICP Standard Solution Beryllium (Be) 1000mg/l in HNO ₃ 2%, HF 0.5% ; nitric acid ; hydrofluoric Acid	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items: Beryllium nitrate (13597-99-4), Hydrogen fluoride (7664-39-3).

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX I RESTRICTED EXPLOSIVES PRECURSORS

List of substances which are not to be made available to, or introduced, possessed or used by, members of the general public, whether on their own or in mixtures or substances that include those substances, unless the concentration is equal to or lower than the limit values set out in column 2, and for which suspicious transactions and significant disappearances and thefts are to be reported within 24 hours.

Name	CAS-No.	Limit value	Upper limit value for licensing under Article 5(3)	Combined Nomenclature (CN) code for a separate chemically defined compound meeting the requirements of Note 1 to Chapter 28 or 29 of the CN, respectively	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Nitric acid	7697-37-2	3 % w/w	10% w/w	ex 2808 00 00	ex 3824 99 96

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

National regulations

Austria

Toxic Substances Ordinance 2000 : Is subject to the Toxic Substances Ordinance 2000.

France

Occupational diseases	
Code	Description
RG 32	Occupational disorders caused by fluoride, hydrofluoric acid and its mineral salts

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).
Chemicals Prohibition Ordinance (ChemVerbotsV) : This product is subject to ChemVerbotsV Annex 2 Entry 1. The following requirements must be observed: authorization requirement (according to § 6 paragraph 1 sentence 1), basic requirements for carrying out the delivery (according to § 8 paragraph 1, 3 and 4), identification and documentation (according to § 9 paragraph 1 to 3) and exclusion of the shipping route (according to § 10).
Major Accidents Ordinance (12. BImSchV) : Is not subject to the Major Accidents Ordinance (12. BImSchV)

Netherlands

ABM category : Z(2) - biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/reprotoxicity/bioaccumulative potential or toxicity)
SZW-lijst van kankerverwekkende stoffen : None of the components are listed
SZW-lijst van mutagene stoffen : None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Poland

Polish National Regulations

: Act of 25 February 2011 on chemical substances and their mixtures (J. o L. No. 63, item 322 as amended; consolidated text J. o L. 2019, item 1225).
Act of 14 December 2012 on waste (J. o L. 2013, item 322 as amended; consolidated text J. o L. 2020, item 797).
The announcement of Marshal of the Sejm of the Republic of Poland dated 19 October 2016 concerning the consolidated text announcement of the decree on the management of packaging and packaging waste (J. o L. 2016, item 1863 as amended).
Decree of the Minister of Environment of 14 December 2014 on the catalogue of waste (J. o L. 2014, item 1923).
Act of 19 August 2011 on the Carriage of Dangerous Goods (J. o L. 2011 No. 227, item 1367 as amended; consolidated text J. o L. 2020, item 154).
Regulation of the Minister of Family, Labour and Social Policy of 12 June 2018 on the highest permissible concentration and intensity of noxious agents for health at work environment (J. o L. item 1286 as amended).
The announcement of Minister of Health dated 9 September 2016 concerning the consolidated text announcement of the decree of the Minister of Health of 30 December 2004 on health and safety at work related to exposure to chemical agents at work (J. o L. of 16 September 2016, item 1488)
Regulation of the Minister of Health of 2 February 2011 on tests and measurements of the noxious agents for health at work environment (J. o L. No. 33, item 166 as amended).
Regulation of the Minister of Environment of 9 December 2003 on particularly hazardous substances to the environment (J. o L. No. 217, item 2141).
ADR Agreement: Government Statement of 13 March 2023 on the entry into force of amendments to Annexes A and B to the Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), signed in Geneva on 30 September 1957 (J. o. L. 2023, item 891)

Switzerland

Chemicals Ordinance (ChemO, SR 813.11)

: Group 1

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes		
Section	Changed item	Comments
4.1	First-aid measures for first aider	Added
4.2	Symptoms/effects after inhalation	Added
4.2	Symptoms/effects after ingestion	Added
4.2	Symptoms/effects after skin contact	Modified
5.1	Unsuitable extinguishing media	Added
5.2	Explosion hazard	Added
5.2	Fire hazard	Added
5.3	Firefighting instructions	Added
6.1	Emergency procedures	Added
6.1	Protective equipment	Added
6.1	General measures	Added
6.3	For containment	Added

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes		
Section	Changed item	Comments
7.1	Additional hazards when processed	Added
7.2	Technical measures	Added
7.2	Packaging materials	Added
7.2	Storage conditions	Modified
13.1	Sewage disposal recommendations	Added
13.1	Additional information	Added
13.1	Regional waste regulation	Added
13.1	Product/Packaging disposal recommendations	Modified
15.1	REACH Annex XVII	Modified
16	Abbreviations and acronyms	Modified

Abbreviations and acronyms:	
ACGIH	American Conference of Government Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
COD	Chemical oxygen demand (COD)
CSA	Chemical safety assessment
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
ED	Endocrine disruptor
EN	European Standard
EWC	European waste catalogue
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:

Log Kow	Partition coefficient n-octanol/water (Log Kow)
Log Pow	Partition coefficient n-octanol/water (Log Pow)
MAK	maximum workplace concentration
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
N.O.S.	Not Otherwise Specified
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
OSHA	Occupational Safety Health Administration
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
PPE	Personal protection equipment
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TF	Technical function
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
TWA	Time Weighted Average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative
UFI	Unique Formula Identifier

Full text of H- and EUH-statements:

Acute Tox. 1 (Dermal)	Acute toxicity (dermal), Category 1
Acute Tox. 1 (Inhalation)	Acute toxicity (inhal.), Category 1
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 2 (Oral)	Acute toxicity (oral), Category 2
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Carc. 1B	Carcinogenicity (inhalation) Category 1B
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Met. Corr. 1	Corrosive to metals, Category 1
Ox. Liq. 2	Oxidising Liquids, Category 2
Ox. Liq. 3	Oxidising Liquids, Category 3
Ox. Sol. 2	Oxidising Solids, Category 2

ICP Standard Solution

Beryllium (Be) 1000mg/l in HNO₃ 2%, HF 0.5%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:

Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H300	Fatal if swallowed.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.
H350i	May cause cancer by inhalation.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Acute Tox. 4 (Oral)	H302	Calculation method
Acute Tox. 3 (Dermal)	H311	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 1B	H350	Calculation method
STOT RE 2	H373	Calculation method

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.