

Nitric acid 1M -spectracer Volumetric solution.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Version: 1.2

Date of issue: 09/08/2014

Revision date: 12/20/2016

	Date of Is	sue: 09/08/2014	Revision date: 12/20/	2016 Version: 1.2	
SECTION 1: Ic	dentification				
1.1. Identific					
Product form		: Mixture			
Product name		: Nitric acid 1M			
		Volumetric solu	ition		
Product code		: VL244			
	mended use and restrictions				
Use of the substar			nce material for labor	atory use	
		. Ocraned refere			
1.3. Supplier Spectracer UK Ltd. Second Floor, Second Floor, 27 Gloucester Place, London, W1U 8HU, United Kingdom. Tel: +44 (0) 207 193 9114 Fax:+44 (0) 203 432 4686 Email: contact@spectracer.co.uk					
Web: www.spectra	acer.com				
1.4. Emerge	ncy telephone number				
Emergency number	er	For Chemical E	3445260 Option 1. Emergencies Only ty Advisors) Europe I	Language: English only. .td	
Country	Organization/Company	Address		Emergency number	Comment
Mexico	Servicio de Informacion Toxicologica Sintox	Tintoreto #32 E Nochebuena M México, D.F.	dif. a Desp. Col. xcoac	1 800 009 2800 +52 55 5611 2634 /+52 55 5598 9095	
USA	American Association of Poison Control Centers			1-800-222-1222	
	lazard(s) identification				
2.1. Classifie	cation of the substance or m	nixture			
GHS-US classific	ation				
Corrosive to metal	s H290	May be	corrosive to metals		
Category 1 Skin corrosion/irrita Category 1A	ation H314	Cause	s severe skin burns a	nd eye damage	
Full text of H statements : see section 16					
2.2 0401-	hal alamanta including area		unto		
2.2. GHS La GHS-US labeling	bel elements, including prec	autionary statem	1115		
Hazard pictograms	s (GHS-US)				
Protogram		GHS05			
Signal word (GHS-US) : Danger					
Hazard statements		: H290 - May be	corrosive to metals severe skin burns ar	id eye damage	
Precautionary state	ements (GHS-US)	P260 - Do not P280 - Wear p P301+P330+P	331 - If swallowed: rin	s/mist/vapors/spray ctive clothing/eye protectior se mouth. Do NOT induce	
10/00/0010			,		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

skin with water/shower
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove con
lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a poison center/doctor/

- P310 Immediately call a poison center/doctor/... P363 Wash contaminated clothing before reuse
- P390 Absorb spillage to prevent material damage
- P405 Store locked up

P501 - Dispose of contents/container to ...

2.3. Other hazards which do not result in classification

No additional information available

Unknown acute toxicity (GHS US) 2.4.

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. **Mixture**

Name	Product identifier	%	GHS-US classification
nitric acid	(CAS No) 7697-37-2	5 - 15	Ox. Liq. 3, H272 Met. Corr. 1, H290 Skin Corr. 1A, H314

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	 Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.
4.2. Most important symptoms and effect	ts (acute and delayed)
Symptoms/injuries after skin contact	: Burns.
Symptoms/injuries after eye contact	: Serious damage to eyes.
Symptoms/injuries after ingestion	: Burns.
4.3. Immediate medical attention and sp	ecial treatment, if necessary
Treat symptomatically.	
Treat symptomatically. SECTION 5: Fire-fighting measures	
, , , , , , , , , , , , , , , , , , ,	ing media
SECTION 5: Fire-fighting measures	ing media : Water spray. Dry powder. Foam. Carbon dioxide.
SECTION 5: Fire-fighting measures 5.1. Suitable (and unsuitable) extinguish	: Water spray. Dry powder. Foam. Carbon dioxide.
SECTION 5: Fire-fighting measures 5.1. Suitable (and unsuitable) extinguish Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
SECTION 5: Fire-fighting measures5.1.Suitable (and unsuitable) extinguishSuitable extinguishing media5.2.Specific hazards arising from the ch	: Water spray. Dry powder. Foam. Carbon dioxide.
SECTION 5: Fire-fighting measures 5.1. Suitable (and unsuitable) extinguish Suitable extinguishing media 5.2. Specific hazards arising from the ch Reactivity	: Water spray. Dry powder. Foam. Carbon dioxide.
SECTION 5: Fire-fighting measures5.1.Suitable (and unsuitable) extinguishSuitable extinguishing media5.2.Specific hazards arising from the chReactivity5.3.Special protective equipment and participation	 Water spray. Dry powder. Foam. Carbon dioxide. memical The product is non-reactive under normal conditions of use, storage and transport. recautions for fire-fighters Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
SECTION 5: Fire-fighting measures 5.1. Suitable (and unsuitable) extinguish Suitable extinguishing media 5.2. Specific hazards arising from the ch Reactivity 5.3. Special protective equipment and p Protection during firefighting SECTION 6: Accidental release measures	 Water spray. Dry powder. Foam. Carbon dioxide. memical The product is non-reactive under normal conditions of use, storage and transport. recautions for fire-fighters Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
SECTION 5: Fire-fighting measures 5.1. Suitable (and unsuitable) extinguish Suitable extinguishing media 5.2. Specific hazards arising from the ch Reactivity 5.3. Special protective equipment and p Protection during firefighting SECTION 6: Accidental release measures	 Water spray. Dry powder. Foam. Carbon dioxide. memical The product is non-reactive under normal conditions of use, storage and transport. recautions for fire-fighters Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. SUIRES

Remove contact

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

J.	·····,	
6.1.2.	For emergency responders	
Protectiv	e equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2.	Environmental precautions	
Avoid rel	ease to the environment.	
6.3.	Methods and material for containme	nt and cleaning up
Methods	for cleaning up	: Take up liquid spill into absorbent material.
Other inf	ormation	: Dispose of materials or solid residues at an authorized site.
6.4.	Reference to other sections	
For furth	er information refer to section 13.	
SECTI	ON 7: Handling and storage	
7.1.	Precautions for safe handling	
Precautio	ons for safe handling	: Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Wear personal protective equipment.
Hygiene	measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2.	Conditions for safe storage, includir	ng any incompatibilities
Storage	conditions	: Store in corrosive resistant container with a resistant inner liner. Keep only in original container. Store locked up. Store in a well-ventilated place. Keep cool.
Incompa	tible materials	: Metals.

SECTION 8: Exposure controls/personal protection 8.1. **Control parameters**

nitric acid (7697-37-2)				
ACGIH	ACGIH TWA (ppm)	2 ppm		
ACGIH	ACGIH STEL (ppm)	4 ppm		
ACGIH	Remark (ACGIH)	URT & eye irr; dental erosion		
OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m³		
OSHA	OSHA PEL (TWA) (ppm)	2 ppm		

8.2.	Appropriate engineering controls		
Appropr	iate engineering controls	:	Ensure good ventilation

- ion of the work station.
- Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties					
9.1. Information on basic physical and chemical properties					
Physical state	: Liquid				
Color	 Mixture contains one or more component(s) which have the following colour(s): colorless to yellow On exposure to light: red-brown 				
Odor	 There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour(s): irritating/pungent odor asphyxiating odor 				
Odor threshold	: No data available				
pH	: <2				
Melting point	: Not applicable				
Freezing point	: No data available				
Boiling point	: No data available				
Flash point	: No data available				
Relative evaporation rate (butyl acetate=1)	: No data available				
Flammability (solid, gas)	: Not applicable.				
Vapor pressure	: No data available				
Relative vapor density at 20 °C	: No data available				
Relative density	: No data available				
Solubility	: Miscible with water.				
Log Pow	: No data available				
Auto-ignition temperature	: No data available				
Decomposition temperature	: No data available				
Viscosity, kinematic	: No data available				
Viscosity, dynamic	: No data available				
Explosion limits	: No data available				
Explosive properties	: No data available				
Oxidizing properties	: No data available				
9.2. Other information					
No additional information available					

No additional information available

SECTI	ON 10: Stability and reactivity				
10.1.	Reactivity				
The proc	The product is non-reactive under normal conditions of use, storage and transport.				
10.2.	Chemical stability				
Stable u	nder normal conditions.				
10.3.	Possibility of hazardous reactions				
No dang	erous reactions known under normal conditions of use.				
10.4.	Conditions to avoid				
None un	der recommended storage and handling conditions (see section 7).				
10.5.	Incompatible materials				
metals.					
10.6.	Hazardous decomposition products				
Under no	ormal conditions of storage and use, hazardous decomposition products should not be produced.				
SECTI	ON 11: Toxicological information				
11.1.	Information on toxicological effects				

Acute toxicity

: Not classified

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin corrosion/irritation	: Causes severe skin burns and eye damage.
	pH: < 2
Serious eye damage/irritation	: Not classified
	pH: < 2
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after skin contact	: Burns.
Symptoms/injuries after eye contact	: Serious damage to eyes.
Symptoms/injuries after ingestion	: Burns.
SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general	: Before neutralisation, the product may represent a danger to aquatic organisms.
nitric acid (7697-37-2)	
EC50 Daphnia 1	180 mg/l (EC50; 48 h)
LC50 fish 2	72 ppm (LC50; 96 h)
Threshold limit algae 1	> 19 mg/l (EC0)
12.2. Persistence and degradability	
nitric acid (7697-37-2)	
Development and de sue debility	Die de wee de la Utan Niet e welke ekste

nitric acid (7697-37-2)	
Persistence and degradability	Biodegradability: Not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

12.3. Bioaccumulative potential

nitric acid (7697-37-2)	
BCF fish 1	<= 1 (BCF)
Log Pow	-2.3 (OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method)
Bioaccumulative potential	Bioaccumulation: Not applicable.

12.4. Mobility in soil

No additional information available

12.5.	Other adverse effects	
Effect of	n the global warming	: No known effects from this product.
GWPmi	x comment	: No known effects from this product.

SECTION 13: Disposal considerations		
13.1. Disposal methods		
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.	
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.	
Ecology - waste materials	: Avoid release to the environment.	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

Department of Transportation (DOT)
In accordance with DOT
Transport document description

UN-No.(DOT) Proper Shipping Name (DOT) Class (DOT) Packing group (DOT) Hazard labels (DOT)

: UN2031

: 158

: Nitric acid other than red fuming, with not more than 20% nitric acid

: UN2031 Nitric acid other than red fuming, with not more than 20% nitric acid, 8, II

- : 8 Class 8 Corrosive material 49 CFR 173.136
- : II Medium Danger
- : 8 Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx)

- DOT Packaging Bulk (49 CFR 173
- DOT S

. 100	
: 242	
 A6 - For combination packaging, if plastic inner packaging are used, they must be packed in tightly closed metal receptacles before packing in outer packaging. B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized. B47 - Each tank may have a reclosing pressure relief device having a start-to-discharge pressure setting of 310 kPa (45 psig). B53 - Packaging must be made of either aluminum or steel. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T8 - 4 178.274(d)(2) Normal	e 0 e
: None	
: 1L	
: 30 L	
: D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vesse carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.	I
: 157	
: No supplementary information available.	
: UN2031 NITRIC ACID (, other than red fuming, with less than 65% nitric acid), 8, II	
: UN2031	
: NITRIC ACID	
: 8 - Class 8 - Corrosives	
: II - Medium Danger	
: 1L	
: Forbidden	
	 A6 - For combination packaging, if plastic inner packaging are used, they must be packed in tightly closed metal receptacles before packing in outer packaging. B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized. B47 - Each tank may have a reclosing pressure relief device having a start-to-discharge pressure setting of 310 kPa (45 psig). B53 - Packaging must be made of either aluminum or steel. IB2 - Authorized IBCS: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31H2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T8 - 4 178.274(d)(2) Normal Prohibited TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by th following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) an the maximum mean bulk temperature of the liquid during filling the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively. TP12 - This material is considered highly corrosive to steel. None 1 L 30 L D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessec carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded. 157 No supplementary information available. UN2031 NITRIC ACID (, other than red fuming, with less than 65% nitric acid), 8, II

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Passenger Carrying Ship Index	: Forbidden
Transport by sea	
Transport document description (IMDG)	: UN 2031 NITRIC ACID, 8, II
UN-No. (IMDG)	: 2031
Proper Shipping Name (IMDG)	: NITRIC ACID
Class (IMDG)	: 8 - Corrosive substances
Packing group (IMDG)	: II - substances presenting medium danger
Limited quantities (IMDG)	: 1L
Air transport	
Transport document description (IATA)	: UN 2031 Nitric acid, 8, II
UN-No. (IATA)	: 2031
Proper Shipping Name (IATA)	: Nitric acid
Class (IATA)	: 8 - Corrosives

SECTION 15: Regulatory information

15.1. US Federal regulations

Packing group (IATA)

nitric acid (7697-37-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	1000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb

: II - Medium Danger

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

No additional information available

SECT	FION 16: Oth	ner information
Revisio	on date	: 12/20/2016
Full tex	kt of H-phrases:	
Н	1272	May intensify fire; oxidizer
Н	1290	May be corrosive to metals
Н	1314	Causes severe skin burns and eye damage

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard	: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA fire hazard	: 0 - Materials that will not burn.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
HMIS III Rating	•
Health	: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
Flammability	: 0 Minimal Hazard - Materials that will not burn
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.
Personal protection	: C
	C - Safety glasses, Gloves, Synthetic apron
	C - Safety glasses, Gloves, Synthetic apron

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.